

UNIVERSIDAD DE CONCEPCIÓN



CENTRO DE INVESTIGACIÓN EN INGENIERÍA MATEMÁTICA (CI²MA)



**Stability and finite element approximation of phase change
models for natural convection in porous media**

MARIO ÁLVAREZ, BRYAN GOMEZ-VARGAS,
RICARDO RUIZ-BAIER, JAMES WOODFIELD

PREPRINT 2018-26

SERIE DE PRE-PUBLICACIONES

Stability and finite element approximation of phase change models for natural convection in porous media

MARIO ALVAREZ* BRYAN GOMEZ-VARGAS[†]
RICARDO RUIZ-BAIER[‡] JAMES WOODFIELD[§]

Abstract

In this paper we study a phase change problem for non-isothermal incompressible viscous flows. The underlying continuum is modelled as either as a viscous Newtonian fluid where the change of phase is encoded in the viscosity itself, or using a Brinkman-Boussinesq approximation where the solidification process influences the drag directly. We address these and other modelling assumptions and their consequences in the simulation of differentially heated cavity flows of diverse type. A second order finite element method for the primal formulation of the problem in terms of velocity, temperature, and pressure is constructed, and we provide conditions for its stability. We finally present several numerical tests corroborating the accuracy of the numerical scheme as well as illustrating key properties of the model.

Keywords: Natural convection; viscous flow in porous media; finite element methods; change of phase; differentially heated cavity.

Mathematics subject classifications (2000): 65M30, 76M10, 76S05, 80A22.

1 Introduction

The phenomenon of natural convection driven by variations in temperature distribution has been extensively studied from the viewpoint of physical properties and also using computational methods. Common applications include ocean and atmosphere dynamics, design of double glass windows and ventilation devices. If the density of the fluid is approximately constant and the buoyancy contribution depends on temperature, the model equations consist of the so-called Boussinesq approximation [14]. Phenomena that involve phase change in addition to these elements have also a great relevance in many industrial and natural processes, as in e.g. the melting and solidification in the refining of metals.

As the nature of the physical scenario abruptly changes, modelling and computing formalisms usually have difficulties in reproducing the behaviour of the system especially near the liquid-solid

*Sección de Matemática, Sede de Occidente, Universidad de Costa Rica, San Ramón de Alajuela, Costa Rica, email: mario.alvarezguadamuz@ucr.ac.cr.

[†]Sección de Matemática, Sede de Occidente, Universidad de Costa Rica, San Ramón, Costa Rica. Mathematical Institute, University of Oxford, A. Wiles Building, Woodstock Road, Oxford OX2 6GG, UK. Present address: CI²MA and Departamento de Ingeniería Matemática, Universidad de Concepción, Casilla 160-C, Concepción, Chile, email: bgomez@ci2ma.udec.cl.

[‡]Mathematical Institute, University of Oxford, A. Wiles Building, Woodstock Road, Oxford OX2 6GG, UK, email: ruizbaier@maths.ox.ac.uk.

[§]Mathematical Institute, University of Oxford, A. Wiles Building, Woodstock Road, Oxford OX2 6GG, UK, email: james.woodfield@some.ox.ac.uk.

interface. Phase changes have been incorporated into the Boussinesq approximation mainly using two different approaches. One is based on enthalpy-porosity models (as in e.g. [43]), where a jump function arising from the so-called Carman-Kozeny equations (see e.g. [16, 32]) enforces a large drag force in the solid. Alternatively, phase change has been modelled by embedding a jump function into the viscosity, as in e.g. [20]. One objective in the present paper is to give a numerical comparison between these two models. Difficulties in incorporating phase change models are related to the choice of regularisation and jump size parameters. We address this issue with a new viscosity-based model that highlights an appropriate choice of parameters. The model considers the presence of microscopic particles in the solid, which resembles porosity-based models. We choose a transition from fluid to solid having a large gradient, which creates additional numerical challenges.

Recent numerical methods dedicated for phase change Boussinesq models include a class of stabilised discontinuous Galerkin and finite volume methods proposed for porosity-based models in [43] and [49], respectively; and the primal finite element scheme for viscosity-based models, introduced in [20]. However these contributions do not address the stability of the discrete or continuous problems. Theoretical studies are available for other (typically simpler) related stationary models, as natural convection [36, 50] including stabilisation analysis and errors estimates, and also time-dependent Boussinesq-type problems under different contexts in [2, 3, 9, 22, 44, 45]. The discretisation of these problems has been associated with Taylor-Hood finite elements for mass and momentum equations and piecewise quadratic approximations for the temperature (as in [22, 36, 39, 50]), or Taylor-Hood and piecewise linear elements as in [20], the MINI-element and Lagrange elements [3] and also piecewise quadratic, piecewise linear and piecewise quadratic for velocity-pressure-temperature as in [2]. Exactly divergence-free methods are available for the stationary Boussinesq equations [38], and other related mixed formulations including a posteriori error estimates can be found in [6, 10, 17, 18, 27]. Finite volume, finite difference and Lagrangian schemes have also been used to simulate solidification problems [7, 29, 31, 34]. In summary, a large variety of methods could be employed to solve numerically the equations we look at here. However the stability of the numerical methods applied to this specific case has not yet been addressed, and this is precisely another objective of this paper.

The remainder of this paper is structured as follows. Section 2 recalls the model problems of flow and temperature with and without phase change. In Section 3 we derive a weak formulation of the governing equations and outline a solvability and stability analysis. In Section 4 we introduce two finite element methods based on the primal velocity-pressure-temperature formulation and on the mixed-primal stress-velocity-temperature formulation of the generalised Boussinesq equations. We specify the fully discrete implicit scheme and write down the corresponding Newton linearisation. Next, in Section 5 we present several tests serving as numerical validation for the enthalpy-free case, and we then present a set of comparisons and concluding insights drawn from the simulations of the melting case, collected in Section 6. These tests also include a qualitative analysis on the micro-structure and its relationship with our modelling assumptions, and we close with some remarks and discussions on alternative models.

2 Phase-change Boussinesq models

2.1 Main assumptions and model equations

Let $t \in (0, t_f]$ denote time and let us consider an homogeneous and isotropic porous structure occupying a spatial domain $\Omega \subset \mathbb{R}^d$, $d = 2, 3$ and saturated with an incompressible viscous fluid. This fluid has kinematic viscosity ν , thermal expansion coefficient α , and nondimensional specific heat C .

The model problem arises from the description of flow using Navier-Stokes and Stefan problems.

Applying the so-called Obereck-Boussinesq approximation, one ends up with the following set of governing equations written in terms of the velocity $\mathbf{u}(t) : \Omega \rightarrow \mathbb{R}^d$, the pressure $p(t) : \Omega \rightarrow \mathbb{R}$, and the temperature $\theta(t) : \Omega \rightarrow \mathbb{R}$:

$$\partial_t \mathbf{u} + \mathbf{u} \cdot \nabla \mathbf{u} - \frac{1}{\text{Re}} \operatorname{div} [2\mu(\theta)\boldsymbol{\varepsilon}(\mathbf{u})] + \nabla p + \eta(\theta)\mathbf{u} = f(\theta)\mathbf{k}, \quad (2.1)$$

$$\operatorname{div} \mathbf{u} = 0, \quad \text{in } \Omega \times (0, t_f], \quad (2.2)$$

$$\partial_t \theta + \mathbf{u} \cdot \nabla \theta - \frac{1}{C\text{Pr}} \operatorname{div} (\kappa \nabla \theta) + \partial_t s + \mathbf{u} \cdot \nabla s = 0, \quad (2.3)$$

and which state the conservation of momentum, mass, and energy with enthalpy, respectively. In (2.1)-(2.3), $\boldsymbol{\varepsilon}(\mathbf{u}) = \frac{1}{2}(\nabla \mathbf{u} + \nabla \mathbf{u}^T)$ is the strain rate tensor, the function s is the enthalpy, the symbol \mathbf{k} stands for the unit vector pointing in the opposite direction to gravity, η, μ are nonlinear functions of temperature that encode the permeability of the porous material and the viscosity of the fluid, respectively. These functions will assume different specifications depending on the phase change model, to be discussed later on. We also define the Reynolds number $\text{Re} = \rho_{\text{ref}} V_{\text{ref}} L_{\text{ref}} \mu^{-1}$, the adimensional buoyancy force $f(\theta) = \text{Ra}\theta(\text{Pr Re}^2)^{-1}$ (depending linearly on the temperature distribution as in the classical Boussinesq approximation [14]), κ is the adimensional heat conductivity tensor (here assumed isotropic), $\text{Ra} = g\beta L_{\text{ref}}(\theta_h - \theta_c)[\nu\alpha]^{-1}$ is the Rayleigh number, g is the gravity magnitude, $L_{\text{ref}}, \rho_{\text{ref}}, V_{\text{ref}}$ are the reference length, density, and velocity defining the flow, θ_h, θ_c are maximum and minimum temperatures, and $\text{Pr} = \nu\alpha^{-1}$ is the Prandtl number.

In order to analyse the coupled system (2.1)-(2.3), we will suppose that the functions μ, η are uniformly bounded and Lipschitz continuous: there exist positive constants $\mu_1, \mu_2, \eta_1, \eta_2, L_\mu$ and L_η , such that

$$\eta_1 \leq \eta(\psi) \leq \eta_2, \quad |\eta(\psi) - \eta(\varphi)| \leq L_\eta |\psi - \varphi| \quad \forall \psi, \varphi \in \mathbb{R}, \quad (2.4)$$

$$\mu_1 \leq \mu(\psi) \leq \mu_2, \quad |\mu(\psi) - \mu(\varphi)| \leq L_\mu |\psi - \varphi| \quad \forall \psi, \varphi \in \mathbb{R}. \quad (2.5)$$

Similar assumptions will be placed on the source function f : we suppose that there exists positive constants C_f and L_f such that

$$|f(\psi)| \leq C_f |\psi|, \quad |f(\psi) - f(\varphi)| \leq L_f |\psi - \varphi| \quad \forall \psi, \varphi \in \mathbb{R}. \quad (2.6)$$

On the other hand, we will suppose that for every $\psi \in H^1(\Omega)$, we have $s(\psi) \in H^1(\Omega)$, and that there exist positive constants s_1, s_2, L_{s_1} and L_{s_2} such that

$$|s(\psi)| \leq s_1, \quad |s(\psi) - s(\varphi)| \leq L_{s_1} |\psi - \varphi| \quad |\nabla s(\psi)| \leq s_2 |\nabla \psi|, \quad |\nabla s(\psi) - \nabla s(\varphi)| \leq L_{s_2} |\psi - \varphi|, \quad (2.7)$$

for all $\psi, \varphi \in \mathbb{R}$. Finally, we suppose that κ is a uniform bounded and uniformly positive definite tensor, meaning that there exist positive constants κ_0 and κ_1 such that

$$|\kappa| \leq \kappa_1, \quad \kappa \mathbf{v} \cdot \mathbf{v} \geq \kappa_0 |\mathbf{v}|^2 \quad \forall \mathbf{v} \in \mathbb{R}^d. \quad (2.8)$$

Boundary and initial data. Equations (2.1)-(2.3) are supplemented with boundary conditions as follows. No-slip boundary conditions are prescribed on the velocity over the whole $\partial\Omega$, and therefore an additional condition is required for pressure uniqueness; as usual we impose a zero-mean property. Regarding the energy equation, we assume that the domain boundary admits a splitting between two disjoint sets Γ_D^θ and Γ_N^θ , where temperature and normal heat fluxes are prescribed, respectively. The system is supposed to be initially at rest and isothermal, and so we set $\mathbf{u}(0) = \mathbf{0}$, $p(0) = 0$ and $\theta(0) = \theta_0$ with θ_0 constant.

2.2 Enthalpy-porosity models for phase change

The permeability function η appearing in the drag term is usually defined in such a way that (2.1) behaves as the well-known Carman-Kozeny equations (see e.g. the review [40]). That is, one uses a phase change (or liquid fraction) field ϕ with

$$\eta(\phi) = \xi \frac{(1 - \phi)^2}{\phi^3 + m}, \quad \text{with} \quad \phi = \frac{1}{2} \left[\tanh \left(\frac{5}{\delta\theta} (\theta - \theta_f) \right) + 1 \right], \quad (2.9)$$

where $m > 0$ is a small parameter that prevents division by zero. The term $\delta\theta$ represents the temperature range corresponding to the width of the mushy region, and θ_f is a constant the jump function is regularised about and it corresponds to the melting point subject to appropriate scaling (in the sense that in the fluid one has $\phi = 1$ by setting $\eta = 0$, and in the solid $\phi = 0$ corresponds to $\eta = \xi[m]^{-1}$). This also implies that in the solid region one imposes a low permeability field that generates a large drag force. The parameter ξ is a large constant that represents the morphology of the melt front. It is related to the imposed permeability through $\xi = \frac{180}{\rho_{\text{ref}} d_m^2}$ where d_m is the particle diameter, and the constant 180 depends on the material under consideration [11]. Alternatively to (2.9), in our examples we will include a regularised jump function that takes the form

$$\eta = \frac{\eta_s}{2} [\tanh(M_\eta(\theta_f - \theta)) + 1], \quad (2.10)$$

where η_s corresponds to the relative size of the imposed force and M_η is the size of the mushy region. These constants determine the degree of regularisation of the jump. As above, in the liquid phase we have $\eta = 0$, and in the solid $\eta = \eta_s$, with η_s a large constant accounting for the morphology of the melt front.

In many models from the literature, the phase change is often described by combining the permeability (or porosity) regularised jumps with an enthalpy formulation [11]. The non-dimensional enthalpy function s should ideally be a Heaviside function assuming the values s_s in the solid, and s_l in the liquid. After regularisation using the phase change field ϕ we employ

$$s(\theta) = s_s + (s_l - s_s)\phi(\theta). \quad (2.11)$$

We will adopt this form in all of our models, so that the mushy region for the enthalpy will be predetermined by the temperature range $\delta\theta$.

2.3 Enthalpy-viscosity models for phase change

The incorporation of phase change can be alternatively embedded in the form of a temperature-dependent viscosity combined with an enthalpy formulation (as in e.g. [20]). The information about phase variation from solid to fluid is then carried by two different scaled viscosities. This family of models can also be linked to the principle of packing spheres (more naturally associated with the porosity model above, as a dense packing of spheres in the solid translates into a drag force that slows down the flow), and its influence on viscosity variations.

Defining Φ as the ratio of volume occupied by solid particles, we notice that it is related to the phase function ϕ by $\Phi = \Phi_m(1 - \phi)$, where Φ_m is a constant depending on the maximum packing of the imposed particles, and so the latter corresponds to the ratio of volume not corresponding to solid particles. As a given solid melts, then there are less solid particles suspended in the liquid, implying an adequate decrease in the viscosity $\mu = \phi^{-B\Phi_m}$. Defining then $n = B\Phi_m$ and using a security constant

m (mimicking the regularisation in the Carman-Kozeny equation) we obtain

$$\mu = \frac{1}{\phi^n + m}. \quad (2.12)$$

In analogy to (2.10) we will also employ

$$\mu(\theta) = \mu_l + \frac{(\mu_s - \mu_l)}{2} [\tanh(M_\mu(\theta_f - \theta)) + 1], \quad (2.13)$$

so that in the solid we have $\mu = \mu_s$, and in the liquid $\mu = \mu_l$. Here the constant M_μ encodes the width of the mushy region.

2.4 Relationship with the rheology of suspended particles

Historic models for the rheology of suspensions go back to [24], where the relation $\mu = 1 + B\Phi$, with $B = 2.5$ is postulated. This model can be derived by the consideration of slow flow past a sphere, and it corresponds to linear Newton rheology and is only valid for very dilute suspensions ($\Phi \lesssim 0.01$), so it would not be suitable for phase change models. Extensions to the case of particles with varying size were derived from first principles in [12] and [41]. These models also capture the property that the viscosity tends to infinity as the ratio of solid volume to liquid volume tends to 1, and they deal much better with non Newtonian viscosities observed at higher values of Φ . This form of the viscosity model is still used for nano particles [26], or for the sedimentation-consolidation in macroscopic models [42], and it relates to our model of phase change. Traditionally, these models incorporate differences in density and enthalpy by considering nano-particles made of different materials. See for instance [23], where thermal and density properties of copper nano-particles are taken into account. In this context, the models in (2.12) and (2.13) consider nano-particles with the same density and thermal properties, and an important distinction is that the concentration of nano-particles is dependent on temperature in such a way that the particles are not present in the liquid phase, and they exhibit maximum concentration in the solid phase. This is also linked to concept of critical fraction introduced in [41]. There, a packing density becomes high enough that the fluid behaves as a solid, $\mu = (1 - \frac{\Phi}{\Phi_m})^{-2.5}$ where Φ_m is a constant depending on the maximum particle packing, and the model was later extended to $\mu = (1 - \frac{\Phi}{\Phi_m})^{-B\Phi_m}$, see [33].

3 Analysis of Boussinesq phase change models

3.1 Weak formulation

Firstly let us recall some recurrent notation. For instance, we will write $L^2(\Omega)$ to denote the space of square integrable functions, and will use $H^1(\Omega)$, $\mathbf{H}^1(\Omega)$ to refer to the scalar and vector-valued Sobolev spaces $W^{1,2}(\Omega)$ and $\mathbf{W}^{1,2}(\Omega)$, respectively; whose norms will be denoted as $\|\cdot\|_{1,\Omega}$. The inner product in $L^2(\Omega)$ (or in its vectorial and tensorial counterparts) will be simply denoted as (\cdot, \cdot) and its associated norm as $\|\cdot\|$. In addition, the space $L_0^2(\Omega)$ denotes the restriction of $L^2(\Omega)$ to functions with zero mean value over Ω . In view of incorporating the boundary conditions for velocity and temperature, we also introduce the space $\mathbf{H}_0^1(\Omega)$ of vector functions in $\mathbf{H}^1(\Omega)$ whose trace vanishes on $\partial\Omega$, and the space $H_D^1(\Omega)$ of scalar functions in $H^1(\Omega)$ whose trace vanishes on the sub-boundary Γ_D^θ .

Associated with the spaces introduced above, the following nonlinear, bilinear and trilinear forms are defined for all $\mathbf{u}, \mathbf{v}, \mathbf{w} \in \mathbf{H}^1(\Omega)$, $p, q \in L^2(\Omega)$, and $\theta, \psi \in H^1(\Omega)$

$$\begin{aligned} a_1^\theta(\mathbf{u}, \mathbf{v}) &:= \frac{2}{\text{Re}} \int_{\Omega} \mu(\theta) \boldsymbol{\varepsilon}(\mathbf{u}) : \boldsymbol{\varepsilon}(\mathbf{v}), \quad b(\mathbf{v}, q) := - \int_{\Omega} q \operatorname{div} \mathbf{v}, \quad c_1(\mathbf{w}; \mathbf{u}, \mathbf{v}) := \int_{\Omega} [(\mathbf{w} \cdot \nabla) \mathbf{u}] \cdot \mathbf{v}, \\ a_3(\theta, \psi) &:= \frac{1}{C \Pr} \int_{\Omega} \kappa \nabla \theta \cdot \nabla \psi, \quad c_3(\mathbf{w}; \theta, \psi) := \int_{\Omega} [\mathbf{w} \cdot \nabla \theta] \psi. \end{aligned} \quad (3.1)$$

On account of these definitions, we proceed to test (2.1)-(2.2) against adequate functions and integrate by parts conveniently in order to arrive at the following problem in weak form. For all $t \in (0, t_f]$, find $(\mathbf{u}, p, \theta) \in \mathbf{H}_0^1(\Omega) \times L_0^2(\Omega) \times H_D^1(\Omega)$ such that

$$\begin{aligned} (\partial_t \mathbf{u}, \mathbf{v}) + c_1(\mathbf{u}; \mathbf{u}, \mathbf{v}) + a_1^\theta(\mathbf{u}, \mathbf{v}) + (\eta(\theta) \mathbf{u}, \mathbf{v}) + b(\mathbf{v}, p) &= (f(\theta) \mathbf{k}, \mathbf{v}) \quad \forall \mathbf{v} \in \mathbf{H}_0^1(\Omega), \\ b(\mathbf{u}, q) &= 0 \quad \forall q \in L^2(\Omega), \\ (\partial_t[\theta + s], \psi) + c_3(\mathbf{u}; \theta + s, \psi) + a_3(\theta, \psi) &= 0 \quad \forall \psi \in H_D^1(\Omega). \end{aligned} \quad (3.2)$$

The forms defined in (3.1) enjoy the following properties, established in e.g. [13]

$$\begin{aligned} |a_1^\theta(\mathbf{u}, \mathbf{v})| &\leq C \|\mathbf{u}\|_{1,\Omega} \|\mathbf{v}\|_{1,\Omega}, \quad |a_1^\theta(\mathbf{v}, \mathbf{v})| \geq C \|\mathbf{v}\|_{1,\Omega}^2, \\ |a_3(\theta, \psi)| &\leq C \|\theta\|_{1,\Omega} \|\psi\|_{1,\Omega}, \quad |a_3(\psi, \psi)| \geq C \|\psi\|_{1,\Omega}^2, \quad b(\mathbf{v}, q) \leq \|\mathbf{v}\|_{1,\Omega} \|q\|, \\ |c_1(\mathbf{w}; \mathbf{u}, \mathbf{v})| &\leq C \|\mathbf{w}\|_{1,\Omega} \|\mathbf{u}\|_{1,\Omega} \|\mathbf{v}\|_{1,\Omega}, \quad |c_3(\mathbf{w}; \theta, \psi)| \leq C \|\mathbf{w}\|_{1,\Omega} \|\theta\|_{1,\Omega} \|\psi\|_{1,\Omega}, \end{aligned}$$

for all $\mathbf{u}, \mathbf{v}, \mathbf{w} \in \mathbf{H}_0^1(\Omega)$, $p, q \in L^2(\Omega)$, and $\theta, \psi \in H_D^1(\Omega)$. Also, there exists $C > 0$ depending only on the domain, such that

$$\sup_{\mathbf{v} \in \mathbf{H}^1(\Omega) \setminus \mathbf{0}} \frac{b(\mathbf{v}, q)}{\|\mathbf{v}\|_{1,\Omega}} \geq C \|q\|_{0,\Omega} \quad \forall q \in L^2(\Omega). \quad (3.3)$$

We can now define the kernel of the bilinear form $b(\cdot, \cdot)$, characterised by the space of divergence-free velocities \mathbf{V} , as

$$\mathbf{V} = \{\mathbf{v} \in \mathbf{H}_0^1; \operatorname{div} \mathbf{v} = 0 \text{ on } \Omega\}.$$

Thus, based on (3.3) and the definition of \mathbf{V} , the incompressibility condition is included in the functional space and the pressure can be removed from the formulation. That is, problem (3.2) is equivalent to the following problem: For all $t \in (0, t_f]$, find $(\mathbf{u}, \theta) \in \mathbf{V} \times H_D^1$ such that

$$\begin{aligned} (\partial_t \mathbf{u}, \mathbf{v}) + c_1(\mathbf{u}; \mathbf{u}, \mathbf{v}) + a_1^\theta(\mathbf{u}, \mathbf{v}) + (\eta(\theta) \mathbf{u}, \mathbf{v}) &= (f(\theta) \mathbf{k}, \mathbf{v}) \quad \forall \mathbf{v} \in \mathbf{V}, \\ (\partial_t[\theta + s], \psi) + c_3(\mathbf{u}; \theta + s, \psi) + a_3(\theta, \psi) &= 0 \quad \forall \psi \in H_D^1(\Omega), \end{aligned} \quad (3.4)$$

(a proof can be carried out following e.g. [22]). Moreover, one can see that for all $\mathbf{u} \in \mathbf{V}$, $\mathbf{v} \in \mathbf{H}^1(\Omega)$, and $\vartheta, \psi \in H^1(\Omega)$, we have

$$c_1(\mathbf{u}; \mathbf{v}, \mathbf{v}) = 0, \quad c_3(\mathbf{u}, \psi, \psi) = 0, \quad c_3(\mathbf{u}; \psi, \vartheta) = -c_3(\mathbf{u}; \vartheta, \psi).$$

3.2 Stability analysis

Note also that the convective and advective terms can be rewritten using skew-symmetric forms as follows

$$c_1(\mathbf{w}; \mathbf{u}, \mathbf{v}) = \frac{1}{2} \int_{\Omega} [(\mathbf{w} \cdot \nabla) \mathbf{u}] \cdot \mathbf{v} - \frac{1}{2} \int_{\Omega} [(\mathbf{w} \cdot \nabla) \mathbf{v}] \cdot \mathbf{u}, \quad c_3(\mathbf{w}; \theta, \psi) = \frac{1}{2} \int_{\Omega} [\mathbf{w} \cdot \nabla \theta] \psi - \frac{1}{2} \int_{\Omega} [\mathbf{w} \cdot \nabla \psi] \theta. \quad (3.5)$$

Single phase flows. Let us consider an enthalpy-free counterpart of (3.2), and proceed to derive energy estimates. Testing the energy equation against the temperature solution, and using (3.5) we obtain

$$\frac{1}{2}\partial_t\|\theta\|_{0,\Omega}^2 + \frac{\kappa}{\text{Pr}}\|\nabla\theta\|_{0,\Omega}^2 = 0,$$

and then one can use Gronwall's lemma to assert that

$$\|\theta\|_{0,\Omega}^2 + \int_0^t \frac{2\kappa}{\text{Pr}}\|\nabla\theta\|_{0,\Omega}^2 ds \leq \|\theta_0\|_{0,\Omega}^2.$$

Testing now the momentum equation against the velocity solution, exploiting again (3.5), and applying Cauchy-Schwarz inequality we obtain

$$\partial_t\|\mathbf{u}\|_{0,\Omega}^2 + \left\| \frac{2\mu(\theta)^{0.5}}{\text{Re}^{0.5}}\boldsymbol{\varepsilon}(\mathbf{u}) \right\|_{0,\Omega}^2 + 2A\|\mathbf{u}\|_{0,\Omega}^2 \leq A_1^2\|\theta_0\|_{0,\Omega}^2 + \|\mathbf{u}\|_{0,\Omega}^2,$$

where we have also used that $|\mathbf{k}| = 1$. We can then invoke Gronwall's lemma once again to get

$$\|\mathbf{u}\|_{0,\Omega}^2 + \int_0^t \left\| \frac{2\mu(\theta)^{0.5}}{\text{Re}^{0.5}}\boldsymbol{\varepsilon}(\mathbf{u}) \right\|_{0,\Omega}^2 ds \leq \exp((1 - 2A)t)(\|\mathbf{u}_0\|_{0,\Omega}^2 + \int_0^t A_1^2\|\theta_0\|_{0,\Omega}^2).$$

Enthalpy-based flows. The following two lemmas will be employed to show the stability and uniqueness analysis of (3.2).

Lemma 3.1 *For $d = 2$, there holds*

$$\|\mathbf{v}\|_{4,\Omega}^2 \leq 2^{1/2} \|\mathbf{v}\|_{0,\Omega} \|\mathbf{v}\|_{1,\Omega} \quad \forall \mathbf{v} \in \mathbf{H}^1(\Omega).$$

Lemma 3.2 *There holds*

$$\|\boldsymbol{\varepsilon}(\mathbf{v})\|_{0,\Omega}^2 \geq \frac{1}{2}|\mathbf{v}|_{1,\Omega}^2 \quad \forall \mathbf{v} \in \mathbf{H}_0^1(\Omega).$$

We now establish the stability analysis of problem (3.4).

Theorem 3.3 *Assume that $\kappa_0 > k_1 s_2$. Then, for any solution of (3.4) and for any $t \in (0, t_f]$, there exists a constant \tilde{C} depending on $\mu_1, \text{Re}, \eta_1, C_f, \kappa_0, \kappa_1, s_2, C, \text{Pr}, \Omega, t_f$ and c_p (positive constant provided by Poincare's inequality), such that*

$$\|\mathbf{u}\|_{\mathbf{L}^2(0,t;\mathbf{H}_0^1(\Omega))} + \|\theta\|_{\mathbf{L}^2(0,t;\mathbf{H}_D^1(\Omega))} \leq \tilde{C}|\mathbf{k}| \left\{ \|s_0\|_{0,\Omega} + \|\theta_0\|_{0,\Omega} \right\}. \quad (3.6)$$

Proof. Let (\mathbf{u}, θ) be the solution of (3.4). Taking $\mathbf{v} = \mathbf{u}$ in the first equation of (3.4) and applying (2.4), (2.5) and (2.6), we obtain that

$$\frac{1}{2}\partial_t\|\mathbf{u}\|_{0,\Omega}^2 + \frac{2\mu_1}{\text{Re}}\|\boldsymbol{\varepsilon}(\mathbf{u})\|_{0,\Omega}^2 + \eta_1\|\mathbf{u}\|_{0,\Omega}^2 \leq C_f|\mathbf{k}|\|\theta\|_{0,\Omega}\|\mathbf{u}\|_{0,\Omega}.$$

Next, applying Young's inequality with constant $\varepsilon = \frac{\eta_1}{C_f|\mathbf{k}|}$, we find that

$$\frac{1}{2}\partial_t\|\mathbf{u}\|_{0,\Omega}^2 + \frac{2\mu_1}{\text{Re}}\|\boldsymbol{\varepsilon}(\mathbf{u})\|_{0,\Omega}^2 + \frac{\eta_1}{2}\|\mathbf{u}\|_{0,\Omega}^2 \leq \frac{C_f^2|\mathbf{k}|^2}{2\eta_1}\|\theta\|_{0,\Omega}^2.$$

By using lemma 3.2, we deduce that

$$\frac{1}{2}\partial_t \|\mathbf{u}\|_{0,\Omega}^2 + \alpha_1 \|\mathbf{u}\|_{1,\Omega}^2 \leq \frac{C_f^2 |\mathbf{k}|^2}{2\eta_1} \|\theta\|_{0,\Omega}^2,$$

where $\alpha_1 := \min \left\{ \frac{\mu_1}{\text{Re}}, \frac{\eta_1}{2} \right\}$. Now, integrating this equation between 0 and t yields

$$\|\mathbf{u}\|_{0,\Omega}^2 + \|\mathbf{u}\|_{\mathbf{L}^2(0,t;\mathbf{H}_0^1(\Omega))}^2 \leq C_1 |\mathbf{k}|^2 \|\theta\|_{\mathbf{L}^2(0,t;\mathbf{H}_D^1(\Omega))}^2, \quad (3.7)$$

where C_1 is a constant depending on $C_f, \mu_1, \eta_1, \text{Re}, \Omega$ and t_f . Similarly, we take $\psi = \theta + s$ in the third row of (3.2), and apply (2.7) and (2.8) to obtain

$$\frac{1}{2}\partial_t \|\theta + s\|_{0,\Omega}^2 + \frac{\kappa_0}{C\text{Pr}} |\theta|_{1,\Omega}^2 \leq \frac{\kappa_1 s_2}{C\text{Pr}} |\theta|_{1,\Omega}^2.$$

Now, we integrate between 0 and t to obtain

$$\|\theta + s\|_{0,\Omega}^2 + \|\theta\|_{\mathbf{L}^2(0,t;\mathbf{H}_D^1(\Omega))}^2 \leq C_2 \left\{ \|s_0\|_{0,\Omega}^2 + \|\theta_0\|_{0,\Omega}^2 \right\}, \quad (3.8)$$

where $s_0 := s(\theta_0)$ and C_2 is a constant depending on $c_p, C, \text{Pr}, \kappa_0, \kappa_1, s_2, \Omega$ and t_f . Finally, we derive the result (3.6) from (3.7) and (3.8). \square

Theorem 3.4 Assume that the data $\theta_0 \in \mathbf{L}^2(\Omega)$. Then, problem (3.2) has a solution $(\mathbf{u}, p, \theta) \in \mathbf{L}^2(0, t_f; \mathbf{H}_0^1(\Omega)) \times \mathbf{L}^2(0, t_f; \mathbf{L}_0^2(\Omega)) \times \mathbf{L}^2(0, t_f; \mathbf{H}_D^1(\Omega))$.

Proof. It follows from an argument based on Galerkin's method and assumptions (2.4)-(2.7). For more details see [2, Theorem 2.3]. \square

The following result establishes the uniqueness of problem (3.2).

Theorem 3.5 Let $d = 2$. If the problem (3.2) admits a solution $(\mathbf{u}, \theta, p) \in \mathbf{L}^p(0, t_f; \mathbf{W}^{1,r}(\Omega)) \times \mathbf{L}^2(0, t_f; \mathbf{H}_0^1(\Omega)) \times \mathbf{L}^2(0, t_f; \mathbf{L}_0^2(\Omega))$, with $p \geq 4$ and $r \geq 4$, and $L_{s_1} < 1/2$, then this solution is unique.

Proof. Let $(\mathbf{u}_1, p_1, \theta_1)$ and $(\mathbf{u}_2, p_2, \theta_2)$ be two solutions of (3.2). With the aim to prove uniqueness, we denote $\bar{\mathbf{u}} = \mathbf{u}_1 - \mathbf{u}_2$, $\bar{p} = p_1 - p_2$ and $\bar{\theta} = \theta_1 - \theta_2$. Now, from the third equation in (3.2), by adding and subtracting $c_3(\mathbf{u}_2, \theta_1 + s(\theta_1), \psi)$, with $\psi = \bar{\theta} + s(\theta_1) - s(\theta_2)$ and applying Cauchy-Schwarz inequality, we obtain that

$$\begin{aligned} & \frac{1}{2}\partial_t \|\bar{\theta} + s(\theta_1) - s(\theta_2)\|_{0,\Omega}^2 + \frac{1}{C\text{Pr}} \kappa_0 |\bar{\theta}|_{1,\Omega}^2 \\ & \leq \frac{\kappa_1 L_{s_2}}{C\text{Pr}} |\bar{\theta}|_{1,\Omega} \|\bar{\theta}\|_{0,\Omega} + |\theta_1 + s(\theta_1)|_{1,\Omega} \|\bar{\mathbf{u}}\|_{4,\Omega} \|\bar{\theta} + s(\theta_1) - s(\theta_2)\|_{4,\Omega}. \end{aligned}$$

Next, using Lemma 3.1 and Young's inequality with constant ε_3 , we deduce that

$$\begin{aligned} & \frac{1}{2}\partial_t \|\bar{\theta} + s(\theta_1) - s(\theta_2)\|_{0,\Omega}^2 + \frac{1}{C\text{Pr}} \kappa_0 |\bar{\theta}|_{1,\Omega}^2 \\ & \leq \frac{\kappa_1 L_{s_2}}{C\text{Pr}} \left\{ \frac{1}{2\varepsilon_3} |\bar{\theta}|_{1,\Omega}^2 + \frac{\varepsilon_3}{2} \|\bar{\theta}\|_{0,\Omega}^2 \right\} + \frac{1}{\sqrt{2}} |\theta_1 + s(\theta_1)|_{1,\Omega} \|\bar{\mathbf{u}}\|_{0,\Omega} |\bar{\mathbf{u}}|_{1,\Omega} \\ & \quad + \frac{1}{\sqrt{2}} |\bar{\theta} + s(\theta_1) - s(\theta_2)|_{1,\Omega} \|\bar{\theta} + s(\theta_1) - s(\theta_2)\|_{0,\Omega} |\theta_1 + s(\theta_1)|_{1,\Omega}. \end{aligned}$$

Finally, by applying again Young's inequality with constants ε_4 and ε_5 , we get

$$\begin{aligned} & \frac{1}{2}\partial_t\|\bar{\theta} + s(\theta_1) - s(\theta_2)\|_{0,\Omega}^2 + \frac{1}{C\text{Pr}}\kappa_0|\bar{\theta}|_{1,\Omega}^2 \\ & \leq \frac{\kappa_1 L_{s_2}}{C\text{Pr}} \left\{ \frac{1}{2\varepsilon_3}|\bar{\theta}|_{1,\Omega}^2 + \frac{\varepsilon_3}{2}\|\bar{\theta}\|_{0,\Omega}^2 \right\} + \frac{1}{\sqrt{2}} \left\{ \frac{1}{2}\varepsilon_4|\bar{\mathbf{u}}|_{1,\Omega}^2 + \frac{1}{2\varepsilon_4}|\theta_1 + s(\theta_1)|_{1,\Omega}^2\|\bar{\mathbf{u}}\|_{0,\Omega}^2 \right\} \\ & \quad + \frac{1}{\sqrt{2}} \left\{ \varepsilon_5(|\bar{\theta}|_{1,\Omega}^2 + L_{s_2}^2\|\bar{\theta}\|_{0,\Omega}^2) + \frac{(L_{s_1}^2 + 1)}{\varepsilon_5}\|\bar{\theta}\|_{0,\Omega}^2|\theta_1 + s(\theta_1)|_{1,\Omega}^2 \right\}. \end{aligned} \quad (3.9)$$

Analogously, from the first equation in (3.2), adding and subtracting the terms $c_1(\mathbf{u}_2, \mathbf{u}_1, \mathbf{v})$, $(\eta(\theta_2)\mathbf{u}_1, \mathbf{v})$ and $\frac{2}{\text{Re}}(\mu(\theta_2)\varepsilon(\mathbf{u}_1), \varepsilon(\mathbf{v}))$, with $\mathbf{v} = \bar{\mathbf{u}}$, and applying Cauchy-Schwarz inequality, we find that

$$\begin{aligned} & \frac{1}{2}\partial_t\|\bar{\mathbf{u}}\|_{0,\Omega}^2 + \frac{2\mu_1}{\text{Re}}\|\varepsilon(\bar{\mathbf{u}})\|_{0,\Omega}^2 + \eta_1\|\bar{\mathbf{u}}\|_{0,\Omega}^2 \\ & \leq \|\bar{\mathbf{u}}\|_{4,\Omega}^2|\bar{\mathbf{u}}|_{1,\Omega} + \frac{2}{\text{Re}}|((\mu(\theta_1) - \mu(\theta_2))\varepsilon(\mathbf{u}_1), \varepsilon(\bar{\mathbf{u}}))| + L_\eta\|\mathbf{u}_1\|_{0,\Omega}\|\bar{\theta}\|_{4,\Omega}\|\bar{\mathbf{u}}\|_{4,\Omega} + L_f|\mathbf{k}|\|\bar{\theta}\|_{0,\Omega}\|\bar{\mathbf{u}}\|_{0,\Omega}. \end{aligned} \quad (3.10)$$

Thus, on the left hand side of (3.10), we apply Korn inequality, while on the right hand side, for the first, third and fourth term, we apply Young's inequality with constants $\varepsilon_6, \varepsilon_7$ and ε_8 to obtain

$$\begin{aligned} & \frac{1}{2}\partial_t\|\bar{\mathbf{u}}\|_{0,\Omega}^2 + \alpha_3\|\bar{\mathbf{u}}\|_{1,\Omega}^2 \\ & \leq \frac{1}{2}\varepsilon_6|\bar{\mathbf{u}}|_{1,\Omega}^2 + \frac{1}{2\varepsilon_6}\|\bar{\mathbf{u}}\|_{0,\Omega}^2|\mathbf{u}_1|_{1,\Omega}^2 + \frac{2}{\text{Re}}|((\mu(\theta_1) - \mu(\theta_2))\varepsilon(\mathbf{u}_1), \varepsilon(\bar{\mathbf{u}}))| \\ & \quad + \frac{1}{\sqrt{2}}L_\eta\|\mathbf{u}_1\|_{0,\Omega}\left\{\frac{1}{2}\varepsilon_7\|\bar{\theta}\|_{0,\Omega}^2 + \frac{1}{2\varepsilon_7}|\bar{\theta}|_{1,\Omega}^2\right\} + \frac{1}{\sqrt{2}}L_\eta\|\mathbf{u}_1\|_{0,\Omega}\left\{\frac{1}{2\varepsilon_8}|\bar{\mathbf{u}}|_{1,\Omega}^2 + \frac{1}{2}\varepsilon_8\|\bar{\mathbf{u}}\|_{0,\Omega}^2\right\} \\ & \quad + \frac{1}{2}L_f|\mathbf{k}|\left\{\|\bar{\theta}\|_{0,\Omega}^2 + \|\bar{\mathbf{u}}\|_{0,\Omega}^2\right\}, \end{aligned} \quad (3.11)$$

where $\alpha_3 := \min\left\{\frac{\mu_1}{\text{Re}}, \eta_1\right\}$. Now, since the exact solution $\mathbf{u}_1 \in \mathbf{L}^p(0, t_f, \mathbf{W}^{1,r}(\Omega))$, $r \geq 4$, $p \geq 4$, using Hölder's and Young's inequalities with constants r , $r^* := \frac{2r}{r-2}$ and $\varepsilon_9, \varepsilon_{10}$, respectively, to the last term of (3.11), we deduce that

$$\begin{aligned} & \frac{2}{\text{Re}}|((\mu(\theta_1) - \mu(\theta_2))\varepsilon(\mathbf{u}_1), \varepsilon(\bar{\mathbf{u}}))| \leq \frac{2L_\mu}{\text{Re}}\left\{\frac{\varepsilon_9}{2}\|\mathbf{u}_1\|_{1,r,\Omega}\|\bar{\mathbf{u}}\|_{1,\Omega}^2 + \frac{1}{2\varepsilon_9}\|\mathbf{u}_1\|_{1,r,\Omega}\|\bar{\theta}\|_{r^*,\Omega}^2\right\} \\ & \leq \frac{L_\mu\varepsilon_9}{\text{Re}}\|\mathbf{u}_1\|_{1,r,\Omega}\|\bar{\mathbf{u}}\|_{1,\Omega}^2 + \frac{L_\mu}{\varepsilon_9\text{Re}}\|\mathbf{u}_1\|_{1,r,\Omega}\left\{\frac{1}{\sqrt{2}\varepsilon_{10}}\|\bar{\theta}\|_{0,\Omega}^2 + \frac{\varepsilon_{10}}{\sqrt{2}}|\bar{\theta}|_{1,\Omega}^2\right\}. \end{aligned} \quad (3.12)$$

Now, choosing the parameters as

$$\begin{aligned} \varepsilon_3 &= \frac{2\kappa_1 L_{s_2}}{\kappa_0}, \quad \varepsilon_4 = \frac{\alpha_3}{\sqrt{2}}, \quad \varepsilon_5 = \frac{\kappa_0}{2\sqrt{2}C\text{Pr}}, \quad \varepsilon_6 = \frac{\alpha_3}{2}, \quad \varepsilon_7 = \frac{\sqrt{2}C\text{Pr}L_\eta\|\mathbf{u}_1\|_{0,\Omega}}{\kappa_0}, \\ \varepsilon_8 &= \frac{\sqrt{2}L_\eta\|\mathbf{u}_1\|_{0,\Omega}}{\alpha_3}, \quad \varepsilon_9 = \frac{\alpha_3\text{Re}}{4L_\mu\|\mathbf{u}_1\|_{1,r,\Omega}}, \quad \varepsilon_{10} = \frac{\kappa_0\varepsilon_9\text{Re}}{2\sqrt{2}C\text{Pr}L_\mu\|\mathbf{u}_1\|_{1,r,\Omega}}, \end{aligned}$$

we obtain from (3.9), (3.11) and (3.12) that

$$\begin{aligned} & \frac{1}{2}\partial_t(\|\bar{\theta} + s(\theta_1) - s(\theta_2)\|_{0,\Omega}^2 + \|\bar{\mathbf{u}}\|_{0,\Omega}^2) \\ & \leq \bar{C}(|\theta_1 + s(\theta_1)|_{1,\Omega}^2 + \|\mathbf{u}_1\|_{1,r,\Omega}^4 + \|\mathbf{u}_1\|_{0,\Omega}^2 + 1)(\|\bar{\mathbf{u}}\|_{0,\Omega}^2 + \|\bar{\theta}\|_{0,\Omega}^2). \end{aligned}$$

Integrating between 0 and t on the last inequality, and then, adding on both sides the term $(|\theta|, |s(\theta_1) - s(\theta_2)|)$, and using the assumption given in the theorem statement, we get

$$\|\bar{\theta}\|_{0,\Omega}^2 + \|\bar{\mathbf{u}}\|_{0,\Omega}^2 \leq \widehat{C} \int_0^t (|\theta_1 + s(\theta_1)|_{1,\Omega}^2 + \|\mathbf{u}_1\|_{1,r,\Omega}^4 + \|\mathbf{u}_1\|_{0,\Omega}^2 + 1) (\|\bar{\mathbf{u}}\|_{0,\Omega}^2 + \|\bar{\theta}\|_{0,\Omega}^2) dt.$$

Finally, by applying Gronwall's lemma, we obtain $\bar{\mathbf{u}} = \mathbf{0}$ and $\bar{\theta} = 0$. Moreover, from the relation

$$(\operatorname{div} \mathbf{v}, \bar{p}) = 0 \quad \forall \mathbf{v} \in \mathbf{H}_0^1(\Omega),$$

we deduce $\bar{p} = 0$, concluding the proof. \square

4 Two families of finite element schemes

Let $\{\mathcal{T}_h\}_{h>0}$ be a shape-regular family of partitions of the region $\bar{\Omega}$, by triangles (or tetrahedrons in 3D) K of diameter h_K , with overall meshsize $h := \max\{h_K : K \in \mathcal{T}_h\}$. In what follows, given an integer $k \geq 1$ and a subset S of \mathbb{R}^d , $\mathbb{P}_k(S)$ will denote the space of polynomial functions defined locally in S and being of total degree $\leq k$.

4.1 A conforming method in primal formulation

The spatial discretisation will be based on the finite element method. Accordingly, we define the following finite-dimensional spaces for the approximation of velocity, pressure, and temperature respectively:

$$\begin{aligned} \mathbf{V}_h &:= \{\mathbf{v}_h \in \mathbf{H}^1(\Omega) : \mathbf{v}_h|_K \in [\mathbb{P}_{k+1}(K)]^d \ \forall K \in \mathcal{T}_h, \text{ and } \mathbf{v}_h = \mathbf{0} \text{ on } \partial\Omega\}, \\ Q_h &:= \{q_h \in L^2(\Omega) : q_h|_K \in \mathbb{P}_k(K) \ \forall K \in \mathcal{T}_h, \text{ and } \int_{\Omega} q_h = 0\}, \\ Z_h &:= \{\psi_h \in H^1(\Omega) : \psi_h|_K \in \mathbb{P}_{k+1}(K) \ \forall K \in \mathcal{T}_h, \text{ and } \psi_h = 0 \text{ on } \Gamma_D^\theta\}, \end{aligned} \quad (4.1)$$

for $k \geq 1$, which satisfy the discrete inf-sup condition: There exists a constant $C^* \geq 0$ independent of h such that

$$\sup_{v_h \in \mathbf{V}_h \setminus \mathbf{0}} \frac{b(v_h, q_h)}{\|v_h\|_{1,\Omega}} \geq C^* \|q_h\|_{0,\Omega} \quad \forall q_h \in Q_h. \quad (4.2)$$

Then the semi-discrete Galerkin method associated with (3.2) reads: For all $t \in (0, t_f]$, find $(\mathbf{u}_h, p_h, \theta_h) \in \mathbf{V}_h \times Q_h \times Z_h$ such that

$$\begin{aligned} (\partial_t \mathbf{u}_h, \mathbf{v}_h) + c_1(\mathbf{u}_h; \mathbf{u}_h, \mathbf{v}_h) + a_1^{\theta_h}(\mathbf{u}_h, \mathbf{v}_h) + (\eta(\theta_h)\mathbf{u}_h, \mathbf{v}_h) + b(\mathbf{v}_h, p_h) &= (f(\theta_h)\mathbf{k}, \mathbf{v}_h) \quad \forall \mathbf{v}_h \in \mathbf{V}_h, \\ b(\mathbf{u}_h, q_h) &= 0 \quad \forall q_h \in Q_h, \\ (\partial_t [\theta_h + s_h], \psi_h) + c_3(\mathbf{u}_h; \theta_h + s_h, \psi_h) + a_3(\theta_h, \psi_h) &= 0 \quad \forall \psi_h \in Z_h \end{aligned} \quad (4.3)$$

A fully discrete method will be obtained after applying the method of lines. Regarding the time discretisation of (4.3), and in view of the overall second order space discretisation expected when choosing $k = 1$, we here employ a fully implicit second-order backward differentiation formula (BDF2). This choice provides unconditional stability and permits to take sufficiently large timesteps to reach approximate steady state solutions, should they exist. Let $0 = t^0 < t^1 < \dots < t^N = t_f$ be a uniform partition of the time interval into equi-spaced subintervals of size Δt , then the method reads: starting

from the initial values $\mathbf{u}_h^0, \theta_h^0, \mathbf{u}_h^1, \theta_h^1$ taken as interpolates of the initial data onto \mathbf{V}_h and Z_h , solve for $n = 1, \dots$ the nonlinear system

$$\begin{aligned} & \frac{3}{2\Delta t}(\mathbf{u}_h^{n+1}, \mathbf{v}_h) + c_1(\mathbf{u}_h^{n+1}; \mathbf{u}_h^{n+1}, \mathbf{v}_h) + \frac{1}{2}(\operatorname{div} \mathbf{u}_h^{n+1} \mathbf{u}_h^{n+1}, \mathbf{v}_h) + a_1^{\theta_h^{n+1}}(\mathbf{u}_h^{n+1}, \mathbf{v}_h) \\ & + (\eta(\theta_h^{n+1})\mathbf{u}_h^{n+1}, \mathbf{v}_h) + b(\mathbf{v}_h, p_h^{n+1}) - (f(\theta_h^{n+1})\mathbf{k}, \mathbf{v}_h) = \frac{1}{\Delta t}(2\mathbf{u}_h^n - \frac{1}{2}\mathbf{u}_h^{n-1}, \mathbf{v}_h) \quad \forall \mathbf{v}_h \in \mathbf{V}_h, \\ & b(\mathbf{u}_h^{n+1}, q_h) = 0 \quad \forall q_h \in Q_h, \\ & \frac{3}{2\Delta t}(\theta_h^{n+1} + s_h^{n+1}, \psi_h) + c_3(\mathbf{u}_h^{n+1}; \theta_h^{n+1} + s_h^{n+1}, \psi_h) + \frac{1}{2}(\operatorname{div} \mathbf{u}_h^{n+1} (\theta_h^{n+1} + s_h^{n+1}), \psi_h) \\ & + a_3(\theta_h^{n+1}, \psi_h) = \frac{1}{\Delta t}(2[\theta_h^n + s_h^n] - \frac{1}{2}[\theta_h^{n-1} + s_h^{n-1}], \psi_h) \quad \forall \psi_h \in Z_h, \end{aligned} \tag{4.4}$$

and for $n = 0$ one applies a first order backward Euler method. The main advantage to introduce the additional terms (see [1], for instance) arise from the following stability relations

$$c_1(\mathbf{u}_h; \mathbf{v}_h, \mathbf{v}_h) + \frac{1}{2}(\operatorname{div} \mathbf{u}_h \mathbf{v}_h, \mathbf{v}_h) = c_3(\mathbf{u}_h; \psi_h, \psi_h) + \frac{1}{2}(\operatorname{div} \mathbf{u}_h \psi_h, \psi_h) = 0 \quad \forall \mathbf{u}_h, \mathbf{v}_h \in \mathbf{V}_h, \quad \forall \psi_h \in Z_h.$$

In much the same way as the continuous case, we define $\mathbf{V}_h^* = \{\mathbf{v}_h \in \mathbf{V}_h; b(\mathbf{v}_h, q_h) = 0 \quad \forall q_h \in Q_h\}$ and thanks to the inf-sup condition (4.2), consider the following equivalent problem (see [39], Lemma 3.1): Find $(\mathbf{u}_h^{n+1}, \theta_h^{n+1}) \in \mathbf{V}_h^* \times Z_h$ such that

$$\begin{aligned} & \frac{3}{2\Delta t}(\mathbf{u}_h^{n+1}, \mathbf{v}_h) + c_1(\mathbf{u}_h^{n+1}; \mathbf{u}_h^{n+1}, \mathbf{v}_h) + \frac{1}{2}(\operatorname{div} \mathbf{u}_h^{n+1} \mathbf{u}_h^{n+1}, \mathbf{v}_h) + a_1^{\theta_h^{n+1}}(\mathbf{u}_h^{n+1}, \mathbf{v}_h) \\ & + (\eta(\theta_h^{n+1})\mathbf{u}_h^{n+1}, \mathbf{v}_h) - (f(\theta_h^{n+1})\mathbf{k}, \mathbf{v}_h) = \frac{1}{\Delta t}(2\mathbf{u}_h^n - \frac{1}{2}\mathbf{u}_h^{n-1}, \mathbf{v}_h) \quad \forall \mathbf{v}_h \in \mathbf{V}_h^*, \\ & \frac{3}{2\Delta t}(\theta_h^{n+1} + s_h^{n+1}, \psi_h) + c_3(\mathbf{u}_h^{n+1}; \theta_h^{n+1} + s_h^{n+1}, \psi_h) + \frac{1}{2}(\operatorname{div} \mathbf{u}_h^{n+1} (\theta_h^{n+1} + s_h^{n+1}), \psi_h) \\ & + a_3(\theta_h^{n+1}, \psi_h) = \frac{1}{\Delta t}(2[\theta_h^n + s_h^n] - \frac{1}{2}[\theta_h^{n-1} + s_h^{n-1}], \psi_h) \quad \forall \psi_h \in Z_h. \end{aligned} \tag{4.5}$$

In what follows, we establish the stability result for (4.4), for which the following algebraic identity will be essential: for any real numbers a^{n+1}, a^n and a^{n-1} , we have

$$2(3a^{n+1} - 4a^n + a^{n-1}, a^{n+1}) = |a^{n+1}|^2 + |2a^{n+1} - a^n|^2 + |\Lambda a^n|^2 - |a^n|^2 - |2a^n - a^{n-1}|^2, \tag{4.6}$$

where $\Lambda a^n = a^{n+1} - 2a^n + a^{n-1}$.

Theorem 4.1 *Let $(\mathbf{u}_h^{n+1}, \theta_h^{n+1}) \in \mathbf{V}_h \times Z_h$ be a solution of (4.4). Assume that $\kappa_0 > 2k_1 s_2$. Then,*

$$\begin{aligned} & \|\mathbf{u}_h^{n+1}\|_{0,\Omega}^2 + \|2\mathbf{u}_h^{n+1} - \mathbf{u}_h^n\|_{0,\Omega}^2 + \sum_{m=1}^n \|\Lambda \mathbf{u}_h^m\|_{0,\Omega}^2 + \sum_{m=1}^n \Delta t \|\mathbf{u}_h^{m+1}\|_{1,\Omega}^2 \\ & \leq C_1 (\|\theta_h^1 + s_h^1\|_{0,\Omega}^2 + \|2(\theta_h^1 + s_h^1) - (\theta_h^0 + s_h^0)\|_{0,\Omega}^2 + \|\mathbf{u}_h^1\|_{0,\Omega}^2 + \|2\mathbf{u}_h^1 - \mathbf{u}_h^0\|_{0,\Omega}^2) \end{aligned} \tag{4.7}$$

and

$$\begin{aligned} & \|\theta_h^{n+1} + s_h^{n+1}\|_{0,\Omega}^2 + \|2(\theta_h^{n+1} + s_h^{n+1}) - (\theta_h^n + s_h^n)\|_{0,\Omega}^2 + \sum_{m=1}^n \|\Lambda(\theta_h^m + s_h^m)\|_{0,\Omega}^2 + \sum_{m=1}^n \Delta t |\theta_h^{m+1}|_{1,\Omega}^2 \\ & \leq C_2 (\|\theta_h^1 + s_h^1\|_{0,\Omega}^2 + \|2(\theta_h^1 + s_h^1) - (\theta_h^0 + s_h^0)\|_{0,\Omega}^2). \end{aligned} \tag{4.8}$$

where C_1 and C_2 are constants independent on h and Δt .

Proof. For (4.8), we take $\psi_h = 4(\theta_h^{n+1} + s_h^{n+1})$ in the third equation of (4.4) and use the relation (4.6) to deduce

$$\begin{aligned} & \|\theta_h^{n+1} + s_h^{n+1}\|_{0,\Omega}^2 + \|2(\theta_h^{n+1} + s_h^{n+1}) - (\theta_h^n + s_h^n)\|_{0,\Omega}^2 + \|\Lambda(\theta_h^n + s_h^n)\|_{0,\Omega}^2 + \frac{4\kappa_0}{CPr} \Delta t |\theta_h^{n+1}|_{1,\Omega}^2 \\ & \leq \frac{4s_2\kappa_1}{CPr} \Delta t |\theta_h^{n+1}|_{1,\Omega}^2 + \|\theta_h^n + s_h^n\|_{0,\Omega}^2 + \|2(\theta_h^n + s_h^n) - (\theta_h^{n-1} + s_h^{n-1})\|_{0,\Omega}^2. \end{aligned}$$

Thus, summing this inequality over n , we obtain

$$\begin{aligned} & \|\theta_h^{n+1} + s_h^{n+1}\|_{0,\Omega}^2 + \|2(\theta_h^{n+1} + s_h^{n+1}) - (\theta_h^n + s_h^n)\|_{0,\Omega}^2 + \sum_{m=1}^n \|\Lambda(\theta_h^m + s_h^m)\|_{0,\Omega}^2 \\ & + \frac{4(\kappa_0 - 2\kappa_1 s_2)}{CPr} \sum_{m=1}^n \Delta t |\theta_h^{m+1}|_{1,\Omega}^2 \leq \|\theta_h^1 + s_h^1\|_{0,\Omega}^2 + \|2(\theta_h^1 + s_h^1) - (\theta_h^0 + s_h^0)\|_{0,\Omega}^2. \end{aligned} \quad (4.9)$$

Similarly, taking $\mathbf{v}_h = 4\mathbf{u}_h^{n+1}$ in the first equation of (4.4) and applying (4.6), we find that

$$\begin{aligned} & \|\mathbf{u}_h^{n+1}\|_{0,\Omega}^2 + \|2\mathbf{u}_h^{n+1} - \mathbf{u}_h^n\|_{0,\Omega}^2 + \|\Lambda\mathbf{u}_h^n\|_{0,\Omega}^2 + \frac{8\mu_1}{Re} \Delta t \|\boldsymbol{\varepsilon}(\mathbf{u}_h^{n+1})\|_{0,\Omega}^2 + 4\eta_1 \Delta t \|\mathbf{u}_h^{n+1}\|_{0,\Omega}^2 \\ & \leq \|\mathbf{u}_h^n\|_{0,\Omega}^2 + \|2\mathbf{u}_h^n - \mathbf{u}_h^{n-1}\|_{0,\Omega}^2 + 4C_f |\mathbf{k}| \Delta t \|\theta_h^{n+1}\|_{0,\Omega} \|\mathbf{u}_h^{n+1}\|_{0,\Omega}. \end{aligned}$$

Applying Young's inequality with constant $\varepsilon = \frac{\eta_1}{C_f |\mathbf{k}|}$ and then, Korn's Lemma, we obtain that

$$\begin{aligned} & \|\mathbf{u}_h^{n+1}\|_{0,\Omega}^2 + \|2\mathbf{u}_h^{n+1} - \mathbf{u}_h^n\|_{0,\Omega}^2 + \|\Lambda\mathbf{u}_h^n\|_{0,\Omega}^2 + \min \left\{ \frac{4\mu_1}{Re}, 2\eta_1 \right\} \Delta t \|\mathbf{u}_h^{n+1}\|_{1,\Omega}^2 \\ & \leq \|\mathbf{u}_h^n\|_{0,\Omega}^2 + \|2\mathbf{u}_h^n - \mathbf{u}_h^{n-1}\|_{0,\Omega}^2 + \frac{2C_f^2 |\mathbf{k}|^2}{\eta_1} \Delta t |\theta_h^{n+1}|_{1,\Omega}^2. \end{aligned}$$

Summing over n and using the estimate (4.9), we finally deduce that

$$\begin{aligned} & \|\mathbf{u}_h^{n+1}\|_{0,\Omega}^2 + \|2\mathbf{u}_h^{n+1} - \mathbf{u}_h^n\|_{0,\Omega}^2 + \sum_{m=1}^n \|\Lambda\mathbf{u}_h^m\|_{0,\Omega}^2 + \min \left\{ \frac{4\mu_1}{Re}, 2\eta_1 \right\} \sum_{m=1}^n \Delta t \|\mathbf{u}_h^{m+1}\|_{1,\Omega}^2 \\ & \leq \frac{2C_f^2 |\mathbf{k}|^2}{\eta_1} \sum_{m=1}^n \Delta t |\theta_h^{m+1}|_{1,\Omega}^2 + \|\mathbf{u}_h^1\|_{0,\Omega}^2 + \|2\mathbf{u}_h^1 - \mathbf{u}_h^0\|_{0,\Omega}^2. \end{aligned} \quad (4.10)$$

Finally, from bounds (4.10) and (4.9) we obtain the results (4.7) and (4.8). \square

We now establish the existence of the solution of (4.4).

Theorem 4.2 *Assume that the data satisfy*

$$2k_1 s_2 < \kappa_0 \quad \text{and} \quad 4C_f^2 |\mathbf{k}|^2 + 9s_1^2 < \frac{2}{CPr} \kappa_0 c_p \min \left\{ \frac{\mu_1}{Re}, \eta_1 \right\}. \quad (4.11)$$

Then, problem (4.5) admits at least a solution $(\mathbf{u}_h^{n+1}, \theta_h^{n+1}, p_h^{n+1}) \in \mathbf{V}_h \times Z_h \times Q_h$.

Proof. We proceed analogously as in [22, Thm. 3.2]. For notational convenience, we introduce the following constants

$$\begin{aligned} C_{\mathbf{u}} &= C_1 \left(\|\theta_h^1 + s_h^1\|_{0,\Omega} + \|2(\theta_h^1 + s_h^1) - (\theta_h^0 + s_h^0)\|_{0,\Omega} + \|\mathbf{u}_h^1\|_{0,\Omega} + \|2\mathbf{u}_h^1 - \mathbf{u}_h^0\|_{0,\Omega} \right), \\ C_{\theta} &= C_2 \left(\|\theta_h^1 + s_h^1\|_{0,\Omega} + \|2(\theta_h^1 + s_h^1) - (\theta_h^0 + s_h^0)\|_{0,\Omega} \right). \end{aligned}$$

Now, proceeding by induction on $n \geq 2$, we define a mapping Φ from $\mathbf{V}_h^* \times Z_h$ into itself by

$$\begin{aligned} (\Phi(\mathbf{u}_h^{n+1}, \theta_h^{n+1}), (\mathbf{v}_h, \psi_h)) &= \frac{1}{2\Delta t}(3\mathbf{u}_h^{n+1} - 4\mathbf{u}_h^n + \mathbf{u}_h^{n-1}, \mathbf{v}_h) + c_1(\mathbf{u}_h^{n+1}; \mathbf{u}_h^{n+1}, \mathbf{v}_h) + \frac{1}{2}(\operatorname{div} \mathbf{u}_h^{n+1} \mathbf{u}_h^{n+1}, \mathbf{v}_h) \\ &+ a_1^{\theta_h^{n+1}}(\mathbf{u}_h^{n+1}, \mathbf{v}_h) + (\eta(\theta_h^{n+1})\mathbf{u}_h^{n+1}, \mathbf{v}_h) - (f(\theta_h^{n+1})\mathbf{k}, \mathbf{v}_h) + c_3(\mathbf{u}_h^{n+1}; \theta_h^{n+1} + s_h^{n+1}, \psi_h) + a_3(\theta_h^{n+1}, \psi_h) \\ &+ \frac{1}{2\Delta t}(3(\theta_h^{n+1} + s_h^{n+1}) - 4(\theta_h^n + s_h^n) + (\theta_h^{n-1} + s_h^{n-1}), \psi_h) + \frac{1}{2}(\operatorname{div} \mathbf{u}_h^{n+1} (\theta_h^{n+1} + s_h^{n+1}), \psi_h). \end{aligned} \quad (4.12)$$

We can note that this mapping is well defined and continuous on $\mathbf{V}_h^* \times Z_h$. In order to use Brouwer's fixed-point theorem, we take $(\mathbf{v}_h, \psi_h) = (\mathbf{u}_h^{n+1}, \theta_h^{n+1})$ in (4.12), apply (4.7)-(4.8) and denote $C_3 := \min\{\frac{\mu_1}{\operatorname{Re}}, \eta_1\}$ to get

$$\begin{aligned} (\Phi(\mathbf{u}_h^{n+1}, \theta_h^{n+1}), (\mathbf{u}_h^{n+1}, \theta_h^{n+1})) &\geq C_3 \|\mathbf{u}_h^{n+1}\|_{1,\Omega}^2 - \frac{1}{2\Delta t} \|4\mathbf{u}_h^n - \mathbf{u}_h^{n-1}\|_{0,\Omega} \|\mathbf{u}_h^{n+1}\|_{1,\Omega} - C_f |\mathbf{k}| \|\theta_h^{n+1}\|_{0,\Omega} \times \\ &\quad \|\mathbf{u}_h^{n+1}\|_{1,\Omega} + \frac{\kappa_0}{C\operatorname{Pr}} |\theta_h^{n+1}|_{1,\Omega}^2 - s_1 \|\mathbf{u}_h^{n+1}\|_{0,\Omega} |\theta_h^{n+1}|_{1,\Omega} - \frac{1}{2} s_1 \|\mathbf{u}_h^{n+1}\|_{1,\Omega} \|\theta_h^{n+1}\|_{0,\Omega} \\ &\quad - 3s_1 |\Omega|^{1/2} \|\theta_h^{n+1}\|_{0,\Omega} - \frac{1}{2\Delta t} \|4(\theta_h^n + s_h^n) - (\theta_h^{n-1} + s_h^{n-1})\|_{0,\Omega} \|\theta_h^{n+1}\|_{0,\Omega} \\ &\geq C_3 \|\mathbf{u}_h^{n+1}\|_{1,\Omega}^2 + \frac{\kappa_0 c_p}{C\operatorname{Pr}} \|\theta_h^{n+1}\|_{1,\Omega} - \frac{1}{2\Delta t} \tilde{C}_1 C_u \|\mathbf{u}_h^{n+1}\|_{1,\Omega} - \left(\frac{1}{2\Delta t} \tilde{C}_2 C_\theta - 3s_1 |\Omega|^{1/2} \right) \|\theta_h^{n+1}\|_{1,\Omega} \\ &\quad - \frac{C_f |\mathbf{k}| \varepsilon_1}{2} \|\theta_h^{n+1}\|_{1,\Omega}^2 - \frac{C_f |\mathbf{k}|}{2\varepsilon_1} \|\mathbf{u}_h^{n+1}\|_{1,\Omega}^2 - \frac{3s_1 \varepsilon_2}{4} \|\theta_h^{n+1}\|_{1,\Omega}^2 - \frac{3s_1}{4\varepsilon_2} \|\mathbf{u}_h^{n+1}\|_{1,\Omega}^2. \end{aligned}$$

Now, taking $\varepsilon_1 = \frac{2C_f |\mathbf{k}|}{C_3}$, $\varepsilon_2 = \frac{3s_1}{C_3}$, applying the second inequality given in (4.11), and recalling that $(\alpha + \beta) \geq \sqrt{2}(\alpha^2 + \beta^2)^{1/2} \forall \alpha, \beta \in \mathbb{R}$, we obtain

$$(\Phi(\mathbf{u}_h^{n+1}, \theta_h^{n+1}), (\mathbf{u}_h^{n+1}, \theta_h^{n+1})) \geq \tilde{C}_1 (\|\mathbf{u}_h^{n+1}\|_{1,\Omega}^2 + \|\theta_h^{n+1}\|_{1,\Omega}^2) - \tilde{C}_2 (\|\mathbf{u}_h^{n+1}\|_{1,\Omega}^2 + \|\theta_h^{n+1}\|_{1,\Omega}^2)^{1/2},$$

where $\tilde{C}_1 = \frac{1}{2} \min\{C_3, \frac{\kappa_0 c_p}{C\operatorname{Pr}}\}$ and $\tilde{C}_2 = \max\left\{\frac{1}{2\Delta t} \tilde{C}_1 C_u, \frac{1}{2\Delta t} \tilde{C}_2 C_\theta - 3s_1 |\Omega|^{1/2}\right\}$. So, the right hand side is nonnegative on the sphere of radius $r := \frac{\tilde{C}_2}{\tilde{C}_1}$. Consequently, applying Brouwer's fixed-point theorem, we get the existence of a solution $(\mathbf{u}_h^{n+1}, \theta_h^{n+1})$ of $\Phi(\mathbf{u}_h^{n+1}, \theta_h^{n+1}) = 0$, concluding the proof. \square

It is important to remark here that the existence of solution of system (4.4) could be obtained directly from an application of Brouwer fixed-point theorem. In fact, now we define the auxiliary problem $(\tilde{\Phi}(\mathbf{u}_h^{n+1}, \theta_h^{n+1}, p_h^{n+1}), (\mathbf{v}_h, \psi_h, q_h)) := (\Phi(\mathbf{u}_h^{n+1}, \theta_h^{n+1}), (\mathbf{u}_h^{n+1}, \theta_h^{n+1})) + b(\mathbf{v}_h, p_h^{n+1}) - b(\mathbf{u}_h^{n+1}, q_h)$, which is continuous from $\mathbf{V}_h \times Z_h \times Q_h$ into itself. Thus, when one take $\mathbf{v}_h = \mathbf{u}_h^{n+1}$, $\psi_h = \theta_h^{n+1}$ and $q_h = p_h^{n+1}$, the additional term disappears and the proof would be exactly the same. The following result asserts the unique solvability of (4.4).

Theorem 4.3 *Assume that Δt sufficiently small and that $L_{s_1} < 1/2$. Then the scheme defined in (4.4) has a unique solution.*

Proof. It follows analogously to the proof of Theorem 3.5. For more details see [3, Thm. 5.3]. \square

4.2 A mixed-primal finite element method

Numerical methods based on mixed-primal variational formulations have the advantage that important physical variables (as pseudostress and vorticity) can be approximated directly. Before stating the

corresponding Galerkin scheme, we proceed to derive a mixed-primal weak formulation for the model problem. In order to simplify the exposition of this section we will restrict to the stationary counterpart of (2.1)-(2.3), in this case written as follows

$$\begin{aligned} \mathbf{u} \cdot \nabla \mathbf{u} - \text{Re}^{-1} \operatorname{div}[\mu(\theta) \boldsymbol{\varepsilon}(\mathbf{u})] + \nabla p + \eta(\theta) \mathbf{u} &= f(\theta) \mathbf{k}, \\ \operatorname{div} \mathbf{u} &= 0, \\ -\text{CPr}^{-1} \operatorname{div}(\kappa \nabla \theta) + \mathbf{u} \cdot \nabla \theta + \mathbf{u} \cdot \nabla s(\theta) &= 0, \end{aligned} \quad (4.13)$$

and associated with Dirichlet boundary conditions $\mathbf{u} = \mathbf{u}_D$ and $\theta = 0$ on Γ . Here the velocity datum $\mathbf{u}_D \in \mathbf{H}^{1/2}(\Gamma)$ verifies the compatibility condition $\int_{\Gamma} \mathbf{u}_D \cdot \boldsymbol{\nu} = 0$, where $\boldsymbol{\nu}$ denotes the unit outward normal on Γ . Proceeding as in [5], we introduce the strain rate tensor as an auxiliary unknown

$$\mathbf{t} := \boldsymbol{\varepsilon}(\mathbf{u}) = \nabla \mathbf{u} - \boldsymbol{\gamma} \in \mathbb{L}_{\text{tr}}^2(\Omega),$$

where $\boldsymbol{\gamma} = \boldsymbol{\omega}(\mathbf{u}) \in \mathbb{L}_{\text{skew}}^2(\Omega)$ is the skew-symmetric part of the velocity gradient $\nabla \mathbf{u}$ and the involved functional spaces are

$$\mathbb{L}_{\text{skew}}^2(\Omega) := \left\{ \boldsymbol{\eta} \in \mathbb{L}^2(\Omega) : \boldsymbol{\eta} + \boldsymbol{\eta}^t = \mathbf{0} \right\}, \quad \mathbb{L}_{\text{tr}}^2(\Omega) := \left\{ \mathbf{s} \in \mathbb{L}^2(\Omega) : \mathbf{s} = \mathbf{s}^t \quad \text{and} \quad \operatorname{tr}(\mathbf{s}) = 0 \right\}.$$

Also the total stress (or pseudostress tensor, including diffusive, convective, and pressure contributions) is regarded as a new unknown

$$\boldsymbol{\sigma} := \text{Re}^{-1} \mu(\theta) \mathbf{t} - (\mathbf{u} \otimes \mathbf{u}) - p \mathbb{I}, \quad (4.14)$$

which implies that the second equation in (4.13) together with (4.14) are equivalent to the relations

$$\text{Re}^{-1} \mu(\theta) \mathbf{t} - (\mathbf{u} \otimes \mathbf{u})^d = \boldsymbol{\sigma}^d, \quad \text{and} \quad p = -\frac{1}{n} \operatorname{tr}(\boldsymbol{\sigma} + \mathbf{u} \otimes \mathbf{u}) \quad \text{in } \Omega.$$

Consequently, we arrive at the following coupled system without pressure

$$\text{Re}^{-1} \mu(\theta) \mathbf{t} - (\mathbf{u} \otimes \mathbf{u})^d = \boldsymbol{\sigma}^d \quad \text{in } \Omega, \quad (4.15)$$

$$\mathbf{t} + \boldsymbol{\gamma} = \nabla \mathbf{u} \quad \text{in } \Omega, \quad (4.16)$$

$$\eta(\theta) \mathbf{u} - \operatorname{div} \boldsymbol{\sigma} = f(\theta) \mathbf{k} \quad \text{in } \Omega, \quad (4.17)$$

$$-\text{CPr}^{-1} \operatorname{div}(\kappa \nabla \theta) + \mathbf{u} \cdot \nabla \theta + \mathbf{u} \cdot \nabla s(\theta) = 0 \quad \text{in } \Omega, \quad (4.18)$$

$$\mathbf{u} = \mathbf{u}_D \quad \text{and} \quad \theta = 0 \quad \text{on } \Gamma, \quad (4.19)$$

$$\int_{\Omega} \operatorname{tr}(\boldsymbol{\sigma} + \mathbf{u} \otimes \mathbf{u}) = 0. \quad (4.20)$$

Note that the incompressibility constraint is implicitly present in (4.15), and the pressure being in $L_0^2(\Omega)$ is guaranteed by the equivalent statement in (4.20).

A weak form for this problem is obtained after testing (4.15)-(4.16) against suitable functions and imposing the symmetry of $\boldsymbol{\sigma}$; multiplying (4.17) by $\boldsymbol{\tau} \in \mathbb{H}(\operatorname{div}; \Omega)$, integrating by parts and using the velocity boundary condition in (4.19); and taking a similar weak formulation for the energy equation as in (3.2), appropriately modified to incorporate the temperature boundary data in (4.19). That is, the temperature trial and test space will be

$$H_0^1(\Omega) := \left\{ \psi \in H^1(\Omega) : \psi = 0 \text{ on } \Gamma \right\}.$$

Moreover, the specific structure of the problem and the orthogonal decomposition $\mathbb{H}(\mathbf{div}; \Omega) = \mathbb{H}_0(\mathbf{div}; \Omega) \oplus \mathbb{R}\mathbb{I}$, allows us to look for stresses in the space

$$\mathbb{H}_0(\mathbf{div}; \Omega) := \left\{ \zeta \in \mathbb{H}(\mathbf{div}; \Omega) : \int_{\Omega} \text{tr}(\zeta) = 0 \right\}.$$

The weak formulation then reads: Find $(\mathbf{t}, \boldsymbol{\sigma}, \mathbf{u}, \boldsymbol{\gamma}, \theta) \in \mathbb{L}_{\text{tr}}^2(\Omega) \times \mathbb{H}_0(\mathbf{div}; \Omega) \times \mathbf{H}^1(\Omega) \times \mathbb{L}_{\text{skew}}^2(\Omega) \times \mathbf{H}_0^1(\Omega)$ such that

$$\begin{aligned} \text{Re}^{-1} \int_{\Omega} \mu(\theta) \mathbf{t} : \mathbf{s} - \int_{\Omega} (\mathbf{u} \otimes \mathbf{u})^{\text{d}} : \mathbf{s} - \int_{\Omega} \boldsymbol{\sigma}^{\text{d}} : \mathbf{s} &= 0 \quad \forall \mathbf{s} \in \mathbb{L}_{\text{tr}}^2(\Omega), \\ \int_{\Omega} \mathbf{t} : \boldsymbol{\tau}^{\text{d}} + \int_{\Omega} \boldsymbol{\gamma} : \boldsymbol{\tau} + \int_{\Omega} \mathbf{u} \cdot \mathbf{div} \boldsymbol{\tau} &= \langle \boldsymbol{\tau} \boldsymbol{\nu}, \mathbf{u}_D \rangle_{\Gamma} \quad \forall \boldsymbol{\tau} \in \mathbb{H}_0(\mathbf{div}; \Omega), \\ - \int_{\Omega} \mathbf{v} \cdot \mathbf{div} \boldsymbol{\sigma} - \int_{\Omega} \boldsymbol{\sigma} : \boldsymbol{\eta} + \int_{\Omega} \eta(\theta) \mathbf{u} \cdot \mathbf{v} &= \int_{\Omega} f(\theta) \mathbf{k} \cdot \mathbf{v} \quad \forall (\mathbf{v}, \boldsymbol{\eta}) \in \mathbf{L}^2(\Omega) \times \mathbb{L}_{\text{skew}}^2(\Omega), \\ \text{CPr}^{-1} \int_{\Omega} \kappa \nabla \theta \cdot \nabla \psi &= - \int_{\Omega} \psi \mathbf{u} \cdot \nabla(\theta + s(\theta)) \quad \forall \psi \in \mathbf{H}_0^1(\Omega). \end{aligned}$$

A further inspection of this formulation eventually reveals the lack of sufficient regularity (in particular for velocity and stress), which suggests the use of augmentation techniques in the spirit of e.g. [4]. We therefore incorporate residual, Galerkin-type terms in weak form

$$\begin{aligned} \kappa_1 \int_{\Omega} \{ \boldsymbol{\sigma}^{\text{d}} + (\mathbf{u} \otimes \mathbf{u})^{\text{d}} + \text{Re}^{-1} \mu(\theta) \mathbf{t} \} : \boldsymbol{\tau}^{\text{d}} &= 0 & \forall \boldsymbol{\tau} \in \mathbb{H}_0(\mathbf{div}; \Omega), \\ \kappa_2 \int_{\Omega} \{ \mathbf{div} \boldsymbol{\sigma} - \eta(\theta) \mathbf{u} \} \cdot \mathbf{div} \boldsymbol{\tau} &= - \kappa_2 \int_{\Omega} f(\theta) \mathbf{k} \cdot \mathbf{div} \boldsymbol{\tau} & \forall \boldsymbol{\tau} \in \mathbb{H}_0(\mathbf{div}; \Omega), \\ \kappa_3 \int_{\Omega} \{ \boldsymbol{\varepsilon}(\mathbf{u}) - \mathbf{t} \} \cdot \boldsymbol{\varepsilon}(\mathbf{v}) &= 0 & \forall \mathbf{v} \in \mathbf{H}^1(\Omega), \\ \kappa_4 \int_{\Omega} \{ \boldsymbol{\gamma} - \boldsymbol{\omega}(\mathbf{u}) \} : \boldsymbol{\eta} &= 0 & \forall \boldsymbol{\eta} \in \mathbb{L}_{\text{skew}}^2(\Omega), \end{aligned}$$

where κ_i , $i \in \{1, 2, 3, 4\}$ are positive parameters. Denoting $H := \mathbb{L}_{\text{tr}}^2(\Omega) \times \mathbb{H}_0(\mathbf{div}; \Omega) \times \mathbf{H}^1(\Omega) \times \mathbb{L}_{\text{skew}}^2(\Omega)$, $\vec{\mathbf{t}} := (\mathbf{t}, \boldsymbol{\sigma}, \mathbf{u}, \boldsymbol{\gamma})$, and $\vec{\mathbf{s}} := (\mathbf{s}, \boldsymbol{\tau}, \mathbf{v}, \boldsymbol{\eta})$, we arrive at the following augmented mixed-primal formulation of the initial coupled problem (4.13): Find $(\vec{\mathbf{t}}, \theta) \in H \times \mathbf{H}_0^1(\Omega)$ such that

$$\begin{aligned} \mathbf{A}_{\theta}(\vec{\mathbf{t}}, \vec{\mathbf{s}}) + \mathbf{B}_{\mathbf{u}}(\vec{\mathbf{t}}, \vec{\mathbf{s}}) &= \mathcal{F}_{\theta}(\vec{\mathbf{s}}) + \mathcal{F}_{\mathbf{D}}(\vec{\mathbf{s}}) & \forall \vec{\mathbf{s}} \in H, \\ \mathbf{a}(\theta, \psi) &= \mathcal{G}_{\mathbf{w}, \theta}(\psi) & \forall \psi \in \mathbf{H}_0^1(\Omega), \end{aligned} \tag{4.21}$$

where, given an arbitrary $(\mathbf{w}, \phi) \in \mathbf{H}^1(\Omega) \times \mathbf{H}_0^1(\Omega)$, the forms \mathbf{A}_{ϕ} , $\mathbf{B}_{\mathbf{w}}$, \mathbf{a} , and the functionals \mathcal{F}_{ϕ} , $\mathcal{F}_{\mathbf{D}}$, and $\mathcal{G}_{\mathbf{w}, \phi}$ are defined as

$$\begin{aligned} \mathbf{A}_{\phi}(\vec{\mathbf{t}}, \vec{\mathbf{s}}) &:= \text{Re}^{-1} \int_{\Omega} \mu(\phi) \mathbf{t} : \{ \mathbf{s} - \kappa_1 \boldsymbol{\tau}^{\text{d}} \} + \int_{\Omega} \mathbf{t} : \{ \boldsymbol{\tau}^{\text{d}} - \kappa_3 \boldsymbol{\varepsilon}(\mathbf{u}) \} - \int_{\Omega} \boldsymbol{\sigma}^{\text{d}} : \{ \mathbf{s} - \kappa_1 \boldsymbol{\tau}^{\text{d}} \} \\ &\quad + \int_{\Omega} \mathbf{u} \cdot \mathbf{div} \boldsymbol{\tau} - \int_{\Omega} \mathbf{v} \cdot \mathbf{div} \boldsymbol{\sigma} + \int_{\Omega} \boldsymbol{\gamma} : \boldsymbol{\tau} - \int_{\Omega} \boldsymbol{\sigma} : \boldsymbol{\eta} + \int_{\Omega} \eta(\phi) \mathbf{u} \cdot \{ \mathbf{v} - \kappa_2 \mathbf{div} \boldsymbol{\tau} \} \\ &\quad - \kappa_4 \int_{\Omega} \boldsymbol{\omega}(\mathbf{u}) : \boldsymbol{\eta} + \kappa_2 \int_{\Omega} \mathbf{div} \boldsymbol{\sigma} \cdot \mathbf{div} \boldsymbol{\tau} + \kappa_3 \int_{\Omega} \boldsymbol{\varepsilon}(\mathbf{u}) : \boldsymbol{\varepsilon}(\mathbf{v}) + \kappa_4 \int_{\Omega} \boldsymbol{\gamma} : \boldsymbol{\eta}, \\ \mathbf{B}_{\mathbf{w}}(\vec{\mathbf{t}}, \vec{\mathbf{s}}) &:= \int_{\Omega} (\mathbf{u} \otimes \mathbf{u})^{\text{d}} : \{ \kappa_1 \boldsymbol{\tau}^{\text{d}} - \mathbf{s} \}, \quad \mathbf{a}(\theta, \psi) := \text{CPr}^{-1} \int_{\Omega} \kappa \nabla \theta \cdot \nabla \psi, \\ \mathcal{F}_{\phi}(\vec{\mathbf{s}}) &:= \int_{\Gamma} f(\phi) \mathbf{k} \cdot \{ \mathbf{v} - \kappa_2 \mathbf{div} \boldsymbol{\tau} \}, \quad \mathcal{F}_{\mathbf{D}}(\vec{\mathbf{s}}) := \langle \boldsymbol{\tau} \boldsymbol{\nu}, \mathbf{u}_D \rangle_{\Gamma}, \quad \mathcal{G}_{\mathbf{w}, \phi}(\psi) := - \int_{\Omega} \psi \mathbf{w} \cdot \nabla(\phi + s(\phi)), \end{aligned}$$

for all $\vec{\mathbf{t}}, \vec{\mathbf{s}} \in H$, $\theta, \psi \in H_0^1(\Omega)$.

The solvability of (4.21) can be established by invoking a fixed-point approach between a mixed formulation for the momentum and mass equations and a primal formulation for the energy equation; which can be carried out following [4, 5, 15]. In contrast with those works, the solvability analysis of the Navier-Stokes equations can be done in our case by applying a further fixed-point iteration that relies on existence results for Brinkman equations, and we require four residual terms and the use of Korn's inequality. Since θ lives in $H_0^1(\Omega)$, we can then apply a similar treatment as in [6, 28]. These steps go beyond the scope of the paper and will be addressed in a forthcoming contribution.

The Galerkin scheme and specific finite element subspaces. For each $K \in \mathcal{T}_h$ let us recall the definition of the local Raviart-Thomas space of order k as $\mathbf{RT}_k(K) := \mathbb{P}_k(K)^d \oplus \mathbb{P}_k(K)\mathbf{x}$, where \mathbf{x} is a generic vector in \mathbb{R} . Then, we consider finite-dimensional subspaces $\mathbb{H}_h^\mathbf{t} \subset \mathbb{L}_{\text{tr}}^2(\Omega)$, $\mathbb{H}_h^\sigma \subset \mathbb{H}_0(\mathbf{div}; \Omega)$, $\mathbf{H}_h^\mathbf{u} \subset \mathbf{H}_0^1(\Omega)$, $\mathbb{H}_h^\gamma \subset \mathbb{L}_{\text{skew}}^2(\Omega)$, $\mathbf{H}_h^\theta \subset \mathbf{H}_0^1(\Omega)$ defined as

$$\begin{aligned}\mathbb{H}_h^\mathbf{t} &:= \left\{ \mathbf{s}_h \in \mathbb{L}_{\text{tr}}^2(\Omega) : \quad \mathbf{s}_h|_K \in \mathbb{P}_k(K) \quad \forall K \in \mathcal{T}_h \right\}, \\ \mathbb{H}_h^\sigma &:= \left\{ \boldsymbol{\tau}_h \in \mathbb{H}_0(\mathbf{div}; \Omega) : \quad \mathbf{c}^\mathbf{t} \boldsymbol{\tau}_h|_K \in \mathbf{RT}_k(K) \quad \forall \mathbf{c} \in \mathbb{R}^d, \quad \forall K \in \mathcal{T}_h \right\}, \\ \mathbf{H}_h^\mathbf{u} &:= \left\{ \mathbf{v}_h \in \mathbf{C}(\bar{\Omega}) : \quad \mathbf{v}_h|_K \in \mathbb{P}_{k+1}(K)^d \quad \forall K \in \mathcal{T}_h \right\}, \\ \mathbb{H}_h^\gamma &:= \left\{ \boldsymbol{\eta}_h \in \mathbb{L}_{\text{skew}}^2(\Omega) : \quad \boldsymbol{\eta}_h|_K \in \mathbb{P}_k(K)^{d \times d} \quad \forall K \in \mathcal{T}_h \right\}, \\ \mathbf{H}_h^\theta &:= \left\{ \psi_h \in C(\bar{\Omega}) \cap \mathbf{H}_0^1(\Omega) : \quad \psi_h|_K \in \mathbb{P}_{k+1}(K) \quad \forall K \in \mathcal{T}_h \right\}.\end{aligned}$$

Denoting $H_h := \mathbb{H}_h^\mathbf{t} \times \mathbb{H}_h^\sigma \times \mathbf{H}_h^\mathbf{u} \times \mathbb{H}_h^\gamma$, $\vec{\mathbf{t}}_h := (\mathbf{t}_h, \boldsymbol{\sigma}_h, \mathbf{u}_h, \boldsymbol{\gamma}_h)$, and $\vec{\mathbf{s}}_h := (\mathbf{s}_h, \boldsymbol{\tau}_h, \mathbf{v}_h, \boldsymbol{\eta}_h)$, a Galerkin scheme reads: Find $(\vec{\mathbf{t}}_h, \theta_h) \in H_h \times \mathbf{H}_h^\theta$ such that

$$\begin{aligned}\mathbf{A}_{\theta_h}(\vec{\mathbf{t}}_h, \vec{\mathbf{s}}_h) + \mathbf{B}_{\mathbf{u}_h}(\vec{\mathbf{t}}_h, \vec{\mathbf{s}}_h) &= \mathcal{F}_{\theta_h}(\vec{\mathbf{s}}_h) + \mathcal{F}_D(\vec{\mathbf{s}}_h) \quad \forall \vec{\mathbf{s}}_h \in H_h, \\ \mathbf{a}(\theta_h, \psi_h) &= \mathcal{G}_{\mathbf{u}_h, \theta_h}(\psi_h) \quad \forall \psi_h \in \mathbf{H}_h^\theta.\end{aligned}\tag{4.22}$$

The well-posedness of (4.22) will be also based on a suitable adaptation of the continuous analysis of (4.21) to the present context (see, e.g. [5, 15]).

4.3 Consistent linearisation

Problem (4.4) entails solving a set of nonlinear equations at each timestep. For this we will employ Newton Raphson's method, which features quadratic convergence provided the initial guess is sufficiently close to the zone of attraction. For a generic nonlinear problem $\mathbf{F}(\mathbf{w}) = \mathbf{0}$, one produces a sequence $\{\mathbf{w}^k\}_k$ converging quadratically to \mathbf{w} , through the iterates

$$\mathcal{DF}(\mathbf{w}^k)[\delta\mathbf{w}] = -\mathbf{F}(\mathbf{w}^k) \quad \text{where} \quad \delta\mathbf{w} = \mathbf{w}^{k+1} - \mathbf{w}^k, \quad \mathbf{w}^0 = (\mathbf{u}_h^n, p_h^n, \theta_h^n),$$

where $\mathcal{DF}(\mathbf{v})[\delta v]$ denotes the Gâteaux derivative of the functional \mathbf{F} along the direction δv . Then at each Newton step k we solve the linear problem

$$\begin{aligned}\frac{3}{2\Delta t}(\delta\mathbf{u}_h, \mathbf{v}_h) + c_1(\delta\mathbf{u}_h; \mathbf{u}_h^k, \mathbf{v}_h) + c_1(\mathbf{u}_h^k; \delta\mathbf{u}_h, \mathbf{v}_h) + \frac{2}{\text{Re}}(\mu'(\theta_h^k)\delta\theta_h \boldsymbol{\varepsilon}(\mathbf{u}_h^k), \boldsymbol{\varepsilon}(\mathbf{v}_h)) \\ + \frac{2}{\text{Re}}(\mu(\theta_h^k)\boldsymbol{\varepsilon}(\delta\mathbf{u}_h), \boldsymbol{\varepsilon}(\mathbf{v}_h)) + (\eta'(\theta_h^k)\delta\theta_h \mathbf{u}_h^k, \mathbf{v}_h) + (\eta(\theta_h)\delta\mathbf{u}_h, \mathbf{v}_h) + b(\mathbf{v}_h, \delta p_h) - (f'(\theta_h^k)\delta\theta_h \mathbf{k}, \mathbf{v}_h) \\ = \frac{1}{\Delta t}(2\mathbf{u}_h^n - \frac{1}{2}\mathbf{u}_h^{n-1}, \mathbf{v}_h) + (\mathcal{R}_h^1(\mathbf{u}_h^k, p_h^k, \theta_h^k), \mathbf{v}_h) \quad \forall \mathbf{v}_h \in \mathbf{V}_h,\end{aligned}$$

$$\begin{aligned}
 b(\delta\mathbf{u}_h, q_h) - \gamma(\delta p_h, q_h) &= (\mathcal{R}_h^2(\mathbf{u}_h^k, p_h^k, \theta_h^k), q_h) \quad \forall q_h \in Q_h, \\
 \frac{3}{2\Delta t}(\delta\theta_h + s'(\theta_h)\delta\theta_h, \psi_h) + c_3(\delta\mathbf{u}_h; \theta_h^k + s(\theta_h^k), \psi_h) + c_3(\mathbf{u}_h^k; \delta\theta_h + s'(\theta_h^k)\delta\theta_h, \psi_h) + a_3(\delta\theta_h, \psi_h) \\
 &= \frac{1}{\Delta t}(2[\theta_h^n + s_h^n] - \frac{1}{2}[\theta_h^{n-1} + s_h^{n-1}], \psi_h) + (\mathcal{R}_h^3(\mathbf{u}_h^k, p_h^k, \theta_h^k), \psi_h) \quad \forall \psi_h \in Z_h.
 \end{aligned}$$

where the terms \mathcal{R}_h^i stand for the Newton residuals associated to the momentum, mass, and energy-enthalpy equations.

One readily notes that as we increase the Rayleigh number, the coupling between the Navier-Stokes and the temperature equation becomes stronger. This makes the radius of convergence for the Newton method smaller (see e.g. [25]). As the new initial guess in the time-dependent method is the solution at the previous timestep, this condition reflects on a restriction on the timestep, independently of the CFL condition.

5 Numerical verification

We stress that the zero-mean condition enforcing the uniqueness of the pressure (for the schemes based on the primal finite element formulation from Section 4.1) is implemented using a pressure penalisation approach. All nonlinear systems undergo a Newton linearisation with fixed residual tolerance of 1E-6. In addition, the resulting linear solves are performed with the direct method SuperLU.

5.1 Experimental convergence for the semidiscrete and fully discrete methods

For our first example we produce the error history associated with the finite element approximation. Let us consider the following closed-form solutions to the stationary Boussinesq equations with enthalpy, defined on the unit square domain $\Omega = (0, 1)^2$:

$$\mathbf{u}(x, y) = \begin{pmatrix} \sin(\pi x)^2 \sin(\pi y)^2 \cos(\pi y) \\ -\frac{1}{3} \sin(2\pi x) \sin(\pi y)^3 \end{pmatrix}, \quad p(x, y) = 10(x^4 - y^4), \quad \theta(x, y) = 1 + \sin(\pi x) \cos(\pi y). \quad (5.1)$$

These functions are smooth and they are used to generate non-homogeneous forcing and source terms. The vertical walls constitute Γ_D^θ and the bottom and top lids of the domain conform Γ_N^θ . The temperature-dependent viscosity, porosity, buoyancy, and enthalpy functions are taken as

$$\eta(\theta) := 2 + \tanh(\frac{1}{2} - \theta), \quad \mu(\theta) := \exp(-\theta), \quad f(\theta) := \frac{\text{Ra}}{\text{Pr Re}^2} \theta, \quad s(\theta) := 1 + \tanh(1 - \theta), \quad (5.2)$$

respectively, and the remaining parameters specifying this steady-state version of (2.1)-(2.3) are $\text{Re} = 10$, $\text{Ra} = 100$, $\text{Pr} = 0.71$, $\gamma = 1\text{E-}6$. We then construct a sequence of successively refined meshes for Ω and proceed to compute errors between approximate and exact solutions, together with local convergence rates. The outcome of this error study is depicted in Table 1, which shows optimal convergence $O(h^{k+1})$ for velocity, pressure, and temperature in their natural norms.

The error associated to the time discretisation is assessed by considering the original transient problem, with enthalpy, and employing the following exact solutions (proposed in [22] for the study of the Boussinesq approximation without enthalpy), defined on the three-dimensional domain $\Omega = (0, 1)^3$:

$$\mathbf{u}(x, y, z, t) = \begin{pmatrix} x^2 + xy - z^2 + yz \\ -2xy - \frac{1}{2}y^2 + 2yz - 2xz \\ z^2 + y^2 - x^2 + 3xy \end{pmatrix} \sin(t), \quad p(x, y, z, t) = [x - y + 3z - 3/2] \sin(t),$$

DoF	h	$\ \mathbf{u} - \mathbf{u}_h\ _1$	rate	$\ p - p_h\ $	rate	$\ \theta - \theta_h\ _1$	rate	it
$k = 1$								
84	0.7071	4.4051	—	0.6275	—	0.3791	—	5
268	0.3536	0.8306	2.407	0.1468	2.096	0.1027	1.884	4
948	0.1768	0.1334	2.638	0.0357	2.038	0.02654	1.953	4
3556	0.0884	0.0239	2.478	0.0088	2.013	0.0067	1.983	4
13764	0.0442	0.0051	2.226	0.0022	2.004	0.0017	1.993	4
54148	0.0221	0.0012	2.074	0.0006	2.001	0.0004	1.997	5
214788	0.0110	0.0003	2.015	0.0001	1.999	0.0001	1.999	4
$k = 2$								
172	0.7071	0.8695	—	0.102	—	0.0994	—	4
588	0.3536	0.1741	2.320	0.0145	2.813	0.0130	2.931	5
2164	0.1768	0.0253	2.779	0.0019	2.873	0.0016	2.991	5
8292	0.0884	0.0034	2.907	0.0003	2.928	0.0002	3.000	5
32452	0.0442	0.0004	2.954	3.38e-5	2.949	2.56e-5	3.001	5
128388	0.0221	6.16e-5	2.824	6.36e-6	2.961	3.21e-6	2.997	5
510724	0.0110	1.43e-5	2.983	1.51e-6	2.984	8.01e-7	2.997	4

Table 1: Error history (errors on a sequence of successively refined grids, experimental convergence rates, and Newton iteration count at each refinement level) associated to the spatial discretisation using the finite element spaces (4.1) with $k = 1$ and $k = 2$.

$$\theta(x, y, z, t) = 2 + [x^2 + y^2 + z^2 + 1] \sin(t).$$

The regularity of these solutions implies that the spatial finite element discretisation using a method with $k = 1$ will be machine-precision accurate, and so the total error will practically coincide with the time discretisation error. The temperature-dependent functions are taken as in (5.2). We proceed to discretise the time interval into a sequence of successively refined grids and compute accumulative errors, defined for a generic field scalar or vector field v as $E(v) := [\Delta t \sum_{n=1}^N |v_h^n - v(t^n)|^2]^{1/2}$, up to the adimensional final time $t_f = 1$. The error history is displayed in Table 2, showing a second order convergence, consistent with the BDF2 algorithm employed.

Δt	$E(\mathbf{u})$	rate	$E(p)$	rate	$E(\theta)$	rate	avg(it)
1	0.1355	—	1.2943	—	0.2627	—	5
0.25	0.0176	1.938	0.1640	1.925	0.0329	1.890	4.2
0.0613	0.0023	1.990	0.0251	1.934	0.0041	1.958	4.2
0.0151	0.0003	1.983	0.0032	1.962	0.0005	1.947	4.2

Table 2: Time discretisation errors produced with a BDF2 method on different timestep resolutions, convergence rates, and average number of Newton iterations.

We also generate the error history associated with the mixed-primal discretisation discussed in Section 4.2. The closed-form solutions are those in (5.1) and the model parameters and temperature-dependent functions are as in the first example above; while the stabilisation constants needed for the augmented formulation take the values $\kappa_1 = \kappa_2 = \mu_1 \mu_2^{-2}$, $\kappa_3 = \mu_1/2$, $\kappa_4 = \mu_1/4$ (and where the constants μ_1, μ_2 are the bounds for the viscosity introduced in (2.5)). The problem in this case is solved in terms of strain rate, total stress (including viscous and convective contributions), velocity,

vorticity tensor, and temperature; and each individual error is measured in its natural norm. The error decay and the corresponding convergence rates are reported in Table 3, which confirms an optimal convergence rate. The Newton iteration count is similar to the one observed in Table 1.

DoF	h	$\ \mathbf{t} - \mathbf{t}_h\ $	rate	$\ \boldsymbol{\sigma} - \boldsymbol{\sigma}_h\ _{\text{div}}$	rate	$\ \mathbf{u} - \mathbf{u}_h\ _1$	rate	$\ \boldsymbol{\gamma} - \boldsymbol{\gamma}_h\ $	rate	$\ \theta - \theta_h\ _1$	rate	it
83	0.7071	1.2330	–	1.2681	–	1.5671	–	1.2547	–	1.5651	–	3
283	0.3536	0.6253	0.826	0.7302	0.796	1.0193	0.633	0.7187	0.803	0.8465	0.886	4
1043	0.1768	0.3402	0.904	0.4056	0.847	0.5788	0.803	0.3641	0.895	0.4328	0.967	4
4003	0.0884	0.1764	0.927	0.2003	0.934	0.3077	0.911	0.1842	0.954	0.2177	0.991	4
15683	0.0442	0.0831	0.954	0.1401	0.929	0.1623	0.925	0.0917	1.022	0.1090	0.997	4
62083	0.0221	0.0462	0.960	0.0892	0.972	0.0958	0.946	0.0483	0.972	0.0548	0.998	4
247043	0.0111	0.0247	0.985	0.0426	0.977	0.0521	0.951	0.0258	0.931	0.0274	0.994	4
985603	0.0055	0.0124	0.992	0.0225	0.985	0.0311	0.954	0.0123	1.003	0.0139	0.978	4

Table 3: Error history (errors on a sequence of successively refined grids, experimental convergence rates, and Newton iteration count at each refinement level) associated to the spatial discretisation using the mixed-primal formulation from Section 4.2, using a lowest-order scheme with $k = 0$.

5.2 Benchmark test: natural convection of air

We further validate the numerical method against a well-documented benchmark, the natural convection of air in a differentially heated square cavity $\Omega = (0, 1)^2$. In this problem we do not have the enthalpy terms, we do not consider the temperature-dependent drag contribution, and the viscosity and conduction coefficients are constant. Therefore the scaling of the equations is as follows

$$\begin{aligned} \partial_t \mathbf{u} + \mathbf{u} \cdot \nabla \mathbf{u} - \text{Pr} \Delta \mathbf{u} + \nabla p + \eta(\theta) \mathbf{u} &= \text{Ra} \text{Pr} \theta \mathbf{k}, \\ \operatorname{div} \mathbf{u} &= 0 && \text{in } \Omega \times (0, t_f], \\ \partial_t \theta + \mathbf{u} \cdot \nabla \theta - \Delta \theta &= 0, \end{aligned}$$

where $\mathbf{k} = (0, 1)^T$, and the only non-dimensional parameters and their values are $\text{Ra} = 1\text{E}5$ and $\text{Pr} = 0.71$. We use a constant timestep of $\Delta t = 0.001$ and employ a rather coarse mesh with meshsize $h = \sqrt{2}/64$. The initial conditions on the domain interior are $\mathbf{u}(0) = \mathbf{0}$ and $\theta(0) = 0.5$, and we prescribe $\theta = 1$ on the left and $\theta = 0$ on the right walls of the cavity (also for the initial datum). The upper and lower plates constitute the boundary Γ_N^θ , where we set zero-flux boundary conditions for temperature (representing insulated walls); and on all four sides of the container we impose no-slip velocities $\mathbf{u} = \mathbf{0}$.

The simulation is run until the final, dimensionless time $t_f = 0.5$, using a Taylor-Hood finite element family for the approximation of velocity and pressure (i.e., $k = 1$), and the pressure penalty parameter takes the value $\gamma = 1\text{E}-7$. The flow is driven by the difference of temperature and examples of velocity, pressure and temperature distribution at the final time are depicted in Figure 5.1(a-c). We observe well-defined temperature profiles and the expected recirculation velocity patterns. A more quantitative study is done by extracting the approximate solutions for temperature and vertical velocity on the horizontal midlines at $y = 0.5$ and plotting them against properly rotated published benchmark values from [48] (which were generated using the method of discrete singular convolution). A reasonably close match is confirmed by looking at Figure 5.1(d,e), where we emphasise that our results come from coarse mesh computations.

We carry out further comparisons based on the average Nusselt number on the hot wall of the




Figure 5.1: Velocity, pressure, and temperature profiles for the 2D differentially heated cavity (a,b,c respectively) and comparisons to the benchmark data in [48] (d and e).

cavity, that is, at $x = 0$. The value is here defined as

$$\overline{\text{Nu}} = \left| \int_M \text{Pr} \operatorname{Re} u_1 \theta - \partial_x \theta \right|, \quad (5.3)$$

where M denotes the hot wall, and it encodes the rate of heat transfer along M (including the total flux, even the part coming from advection). We also record the maximum and minimum velocities and temperatures attained on the symmetry lines $x = 0.5$ and $y = 0.5$. The computed values are collected in Table 4, where we also include reference values from the literature (see also [7, 35]).

	Ra	$\overline{\text{Nu}}$	$\max(\hat{u}_{1,h})$	$\max(\hat{u}_{2,h})$	x_∞	y_∞
Computed	10^3	1.105	0.133	0.137	0.177	0.815
Reference value	10^3	1.117	0.136	0.138	0.178	0.813
Computed	10^4	2.002	0.188	0.239	0.117	0.820
Reference value	10^4	2.054	0.192	0.234	0.119	0.823
Computed	10^5	4.430	0.161	0.258	0.068	0.851
Reference value	10^5	4.337	0.153	0.261	0.066	0.855

Table 4: Average Nusselt number (5.3) and maximum velocities on the midplanes attained at $(0.5, y_\infty)$ and $(x_\infty, 0.5)$, computed for different values of the Rayleigh number and compared with respect to reference values from [21].

6 Examples using phase-change models

6.1 Simulating the melting of N-octadecane

We now consider the melting of a solid phase change material (N-octadecane) contained in a square box and subject to heating on the left side of the domain. The problem set up is taken from [20], where the boundary conditions are as above (no-slip velocities on the whole boundary, the temperature has zero flux on the top and bottom walls, and high and low temperatures are maintained on the left and right walls, respectively). The low temperature imposed on the right wall $\theta_C = -0.01$ is lower than the phase change temperature $\theta = 0$, in order to allow the phase change to occur. We here employ a structured mesh of 100000 elements.

We first consider an enthalpy-viscosity model. The model parameters are as follows $\text{Ra} = 3.27\text{E}5$, $\text{Pr} = 56.2$, $\text{Re} = 1$, $\kappa = 1$, $\text{Ste} = 0.045$, high temperature on the left wall $\theta_H = 1$, and size of the mushy region $\delta\theta = 0.1$. We then use (2.11) with $s_l = 0$, $s_s = [\text{Ste}]^{-1}$, and we also employ the regularised viscosity specification (2.13) with the constants $\mu_l = 1$, $\mu_s = 10^8$, $M_\mu = 50$, and $\theta_f = 0$. These values give a constitutive relationship for the phase change that can also be recovered from (2.9) using the phase change function ϕ together with the viscosity $\mu(\phi) = \mu_s + (\mu_l - s_s)\phi$. In that case, the jump is sufficiently large so that the mushy region acts as a solid near the melting point. Notice that in [20] the convection of enthalpy (the last term in the LHS of (2.3)) is neglected. This term is zero almost everywhere, except within the mushy region. So if this region is relatively large, then the term will have an important effect in the generated flow patterns.

Secondly, we use an enthalpy-porosity model having a very similar jump behaviour. We focus on the regularised permeability field (2.10) and setting the parameter values to $\eta_s = 10^8$, $M_\eta = 50$, $\theta_f = 0$. Again, this can be regularised alternatively using the phase change function ϕ and putting $\eta(\phi) = \eta_s(1 - \phi)$ (see also [43]).

In Figure 6.1 we present snapshots of the numerical solutions obtained using an enthalpy-viscosity model (and setting constant drag), and an enthalpy-porosity model (using constant viscosity). After an initial stage where the dynamics of the system are dictated predominantly by heat conduction, the convective effects in the mixture start to dominate and the layer that determines the phase change moves on to the right on the top of the cavity. We can observe that even if the jump definitions are qualitatively similar, substantial differences appear in terms of the pressure profiles in the solid region. The velocity patterns are also different (the porosity-based model permits recirculation even in the solid), but this can be straightforwardly remediated by taking a larger value for η_s . Secondly, we also observe that the phase change boundary is more advanced using the enthalpy-porosity model, and




Figure 6.1: Example 3. Comparison between the melting of N-octadecane using enthalpy-viscosity (a,b,c) and enthalpy-porosity models (d,e,f).

this is more pronounced at the top of the container. In the next set of tests we will address these differences in further detail.

6.2 Changing the size of the mushy region and the jump nonlinearity

In view to investigate the differences between porosity and viscosity based models, we recall that enthalpy-viscosity models can be very sensitive to dynamic viscosity effects, thermal conductivity variations, and the size of the mushy region (see [8]). On the other hand, the enthalpy-porosity model for the melting of gallium, and studied in [43] is sufficiently accurate for a specific mushy region size. We then proceed to vary the size of the mushy region in an adequate manner to conciliate enthalpy-viscosity and enthalpy-porosity models.

We start with different values for M_μ in the enthalpy-viscosity model, and we observe that with large mushy regions one can mimic the results obtained using enthalpy-porosity models. However, smaller mushy regions in enthalpy-viscosity models do not necessarily imply a higher irregularity in the model coefficients, as their counterpart in enthalpy-porosity models need to impose a larger jump in order to prevent unwanted flow in the solid region. The results of mushy region variations in enthalpy-viscosity models are collected in Figure 6.2(a).

A second investigation is done by modifying the degree of nonlinearity in the Brinkman term. Setting the parameters $\xi = 10^{7.4}$, $m = 10^{-2.6}$ in the specification of the enthalpy-porosity model (2.9)




Figure 6.2: Example 4: Contour plots of the phase change depending on the size of the mushy region on enthalpy-viscosity models (a), or on the nonlinearity of the regularisation in enthalpy-porosity models (b).

imply that the permeability η is regularised over the desired mushy region, with a constant larger than 10^8 reducing the flow in the solid region. We recall that ξ is related to the material morphology, and in the context of the study of melting N-octadecane, one could choose a more appropriate value. Also, the phase change function ϕ could be regularised around some artificial melting temperature with a different choice of mushy region $\delta\theta$. A closer inspection of the model coefficients reveals that the present form is equivalent to (2.10) with a mushy region of size $M_\eta = 150$ (which is a large value, especially considering that enthalpy-porosity models require less regularisation than enthalpy-viscosity models).

Making the link with variable viscosity we recall that in the model by Brinkman one has (2.12). We use the value $n = 2.5$, and choose $m = 10^{-8}$ to produce a jump of order 10^8 . Plotting then η it is clear that the phase change function ϕ requires a different parametrisation in order to get the jump over the required mushy region. We then choose $\phi = \frac{1}{2}[\tanh(50(x - 0.074)) + 1]$, and stress that this model is based on the theory of suspended particles and how the packing density affects viscosity.

Again, using (2.12) and varying n , one can mimic the effects of (2.9). Comparisons of the melting fronts produced with these two last family of models are displayed in Figure 6.2(b), whereas a sample of the numerical solutions choosing $n = 5$ (and having the following regularisation of the phase change function $\phi = \frac{1}{2}[\tanh(50(\theta - 0.0366)) + 1]$), and a locally refined mesh are portrayed in Figure 6.3.

6.3 Flow patterns in a local element

We next turn to the simulation of buoyancy-driven flow within a mesoscopic subdomain (or local element) lying on the boundary layer between liquid and solid. In line with the observations made above, the solid phase can be regarded as a porous medium filled with solid particles. It is expected that these obstacles will generate a drag as the one encoded in the macroscopic form (2.9). In a local




Figure 6.3: Example 4. Velocity components, pressure, temperature, and adapted mesh at $t = 160$, using a porosity-viscosity model with $n = 5$.

element of diameter 0.01, we create a so-called blockage arrangement of randomly distributed particles of varying sizes with mean $d_m = 0.0002$ and a 1% variance. The boundary conditions for the flow are different than in the macroscopic case. We impose a slip velocity $\mathbf{u} = (0, 0.01)^T$ on the left wall and no-slip velocities elsewhere. A drag force is imposed on the fluid as passes through the array of particles. The velocity is reduced on a very small interval, but flow is allowed through the permeable field. These observations suggest why a viscosity-based formulation would require a much smaller mushy region in order to produce the same melting front as in porosity-based models. For instance, for the form (2.12) one should consider nano particles that melt at the melting temperature of the material, and have the same properties as the liquid, therefore their only effect on the fluid would be an increased viscosity. This behaviour is achieved by simply by not being fluid and by colliding with each other. This phenomenon amounts to impose a moving permeable field, eventually leading to the formation of a larger mushy region. In summary, in enthalpy-porosity models the particles are fixed and the drag force hinders the flow, whereas for enthalpy-viscosity models, the holes are allowed to move and the amount of fluid present is reduced. An example is given in Figure 6.4, and a somewhat similar study can be found in [30].

Concluding remarks. We have addressed the modelling of phase change in Boussinesq models within porous media. A finite element method has been proposed for its numerical approximation, and we have established stability of the continuous and discrete equations. We have tested the performance of the method using a classical benchmark for air convection, where the scaled viscosity is one, there




Figure 6.4: Example 5. Velocity and pressure profiles on a local element.

is no porosity, and no enthalpy terms. Secondly, we have simulated the melting of a material, where the phase change is incorporated in two alternative ways: either using viscosity or porosity as main effects producing the interface movement. Extensions of this work include the derivation of error estimates, the generalisation of the enthalpy-viscosity and enthalpy-porosity models to include nonlocal contributions and performing further comparisons with alternative models, such as those based on the error function and reviewed in [19, 37]. We would also like to extend the applicability of the methods proposed here, in the study of large scale models including the thermal evolution of magma/ocean interfaces [46], or ice-shelf melting [47]. A preliminary test is given in Figure 6.5 where we have implemented an enthalpy-porosity model to simulate the flow of the antarctic circumpolar current and the ice-shelf melting around Antarctica, using an unstructured mesh consisting of 20500 elements and the transient version of the mixed-primal finite element scheme described in Section 4.2. For a relatively large mushy region we can observe a stabilisation of the recirculation patterns and a concentration of the temperature gradients towards the phase change layer.

Acknowledgements. This work has been partially supported by Vicerrectoría de Investigación, project 540-B7-233, Sede de Occidente, Universidad de Costa Rica; by CONICYT-Chile through the Becas-Chile Programme for foreign students; and by the EPSRC through the research grant EP/R00207X/1.

References

- [1] H. ABBOUT, V. GIRAUT, T. SAYAH, *A second order accuracy for a full discretized time-dependent Navier–Stokes equations by a two-grid scheme*. Numer. Math., 114 (2009), 189–231.
- [2] R. AGROUM, C. BERNARDI, J. SATOURI, *Spectral discretization of the time-dependent Navier–Stokes problem coupled with the heat equation*. Appl. Math. Comp., 268 (2015), 59–82.
- [3] R. ALDBAISSY, F. HECHT, G. MANSOUR, T. SAYAH, *A full discretisation of the time-dependent Boussinesq (buoyancy) model with nonlinear viscosity*. HAL report (2017), available from <https://halshs.archives-ouvertes.fr/halshs-01646611v2>.




Figure 6.5: Temperature profiles at three different times of the phase change dynamics using (2.10).

- [4] J. ALMONACID, G.N. GATICA, AND R. OYARZÚA, *A mixed–primal finite element method for the Boussinesq problem with temperature-dependent viscosity*. CI²MA preprint 2017–18, available from <http://www.ci2ma.udec.cl>.
- [5] J. ALMONACID, G.N. GATICA, R. OYARZÚA, AND R. RUIZ-BAIER, *A new mixed finite element method for the n -dimensional Boussinesq problem with temperature-dependent viscosity*. CI²MA preprint 2018–18, available from <http://www.ci2ma.udec.cl>.
- [6] M. ALVAREZ, G.N. GATICA, R. RUIZ-BAIER, *An augmented mixed–primal finite element method for a coupled flow–transport problem*. ESAIM: Math. Model. Numer. Anal., 49 (2015), no. 5, 1399–1427.
- [7] F. AMPOFO, T.G. KARAYIANNIS, *Experimental benchmark data for turbulent natural convection in an air filled square cavity*. Int. J. Heat Mass Transfer, 46 (2003), 3551–3572.
- [8] S. ARENA, E. CASTI, J. GASIA, L.F. CABEZA, G. CAU, *Numerical simulation of a finned-tube LHTES system: influence of the mushy zone constant on the phase change behaviour*. Energy Procedia 126 (2017) no. 09, 517–524.
- [9] C. BECKERMANN, R. VISKANTA, *Natural convection solid/liquid phase change in porous media*. Int. J. Heat Mass Transf., 31 (1988), no. I, 35–46.
- [10] C. BERNARDI, L. EL ALAOUI, Z. MGHAZLI, *A posteriori analysis of a space and time discretization of a nonlinear model for the flow in partially saturated porous media*. IMA J. Numer. Anal., 34 (2014), no. 3, 1002–1036.
- [11] A.D. BRENT, V.R. VOLLE, K.J. REID, *Enthalpy-porosity technique for modeling convection-diffusion phase change: application to the melting of a pure metal*. Numer. Heat Transfer, 13 (1988), no. 3, 297–318.
- [12] H.C. BRINKMAN, *The viscosity of concentrated suspensions and solutions*, J. Chem. Phys., 20 (1952), 571.
- [13] J. BOLAND, W. LAYTON, *An analysis of the finite element method for natural convection problems*. Numer. Methods Partial Diff. Eqns., 2 (1990), 115–126.
- [14] J. BOUSSINESQ, *Théorie de l’écoulement tourbillonnant et tumultueux des liquides dans les lits rectilignes à grande section*. Gauthier-Villars et fils, 1897.

- [15] J. CAMAÑO, G.N. GATICA, R. OYARZUA AND R. RUIZ-BAIER, *An augmented stress-based mixed finite element method for the Navier-Stokes equations with nonlinear viscosity*. Numer. Methods Partial Differential Equations, 33 (2017), no. 5, 1692–1725.
- [16] P.C. CARMAN, *Fluid flow through granular beds*. Trans. Inst. Chem. Engr. London 15 (1937), 150–166.
- [17] E. COLMENARES, G.N. GATICA, R. OYARZÚA, *Fixed point strategies for mixed variational formulations of the stationary Boussinesq problem*. Compt. Rend. Math., 354 (2016), no. 1, 57–62.
- [18] E. COLMENARES, M. NEILAN, *Dual-mixed finite element methods for the stationary Boussinesq problem*. Comp. Math. Appl., 72 (2016), 1828–1850.
- [19] A. COSTA, *Viscosity of high crystal content melts: Dependence on solid fraction*. Geophys. Res. Letters, 32 (2005) no. 22.
- [20] I. DANAILA, R. MOGLAN, F. HECHT, S. LE MASSON, *A Newton method with adaptive finite elements for solving phase-change problems with natural convection*. J. Comput. Phys., 274 (2014), 826–840.
- [21] G. DE VAHL DAVIS, *Natural convection of air in a square cavity: A benchmark numerical solution*. Int. J. Numer. Meth. Fluids, 3 (1983), no. 3, 249–264.
- [22] J. DETEIX, A. JENDOUBI, D. YAKOUBI, *A coupled prediction scheme for solving the Navier-Stokes and convection-diffusion equations*. SIAM J. Numer. Anal., 52 (2014), no. 5, 2415–2439.
- [23] N.S. DHAI DAN, J. KHODADADI, T.A. AL-HATTAB, S.M. AL-MASHAT, *Experimental and numerical study of constrained melting of n-octadecane with CuO nanoparticle dispersions in a horizontal cylindrical capsule subjected to a constant heat flux*. Int. J. Heat Mass Transfer, 67 (2013), 523–534.
- [24] A. EINSTEIN, *Eine neue Bestimmung der Molekuldimensionen*, Ann. Physik, 19 (1906), 286–306.
- [25] H.C. ELMAN, D.J. SILVESTER, A.J. WATHEN, *Finite Elements and Fast Iterative Solvers: with Applications in Incompressible Fluid Dynamics*, second ed., Oxford University Press, 2014.
- [26] K. ENSSLIN, *Quantum physics in quantum dots. Nanophysics: Coherence and transport*. École d’été de Physique des Houches, Session LXXXI Les Houches, (2005) 585–586.
- [27] M. FARHLOUL, S. NICIAISE, L. PAQUET, *A mixed formulation of Boussinesq equations: Analysis of non-singular solutions*. Math. Comp., 69 (2000), no. 231, 965–986.
- [28] G.N. GATICA, B. GOMEZ-VARGAS AND R. RUIZ-BAIER, *Analysis and mixed-primal finite element discretisations for stress-assisted diffusion problems*. Comput. Methods Appl. Mech. Engrg., (2018), no. 337, 411–438.
- [29] S.C. GUPTA, *A moving grid numerical scheme for multi-dimensional solidification with transition temperature range*. Comput. Methods Appl. Mech. Engrg., 189 (2000), no. 2, 525–544.
- [30] D. IYI, R. HASAN, *Natural convection flow and heat transfer in an enclosure containing staggered arrangement of blockages*. Proc. Engrg., 105 (2015), 176–183.
- [31] T.A. KOWALEWSKI, M. REBOW, *Freezing of water in a differentially heated cubic cavity*. Int. J. Comput. Fluid Dyn., 11 (1999), no. 3-4, 193–210.
- [32] J. KOZENY, *Ueber kapillare Leitung des Wassers im Boden*. Sitzungsber Akad. Wiss. Wien, 136 (1927), no. 2a, 271–306.
- [33] I.M. KRIEGER, T.J. DOUGHERTY, *A mechanism for non-Newtonian flow in suspension of rigid spheres*, Trans. Soc. Rheol., 3 (1959), 137–152.
- [34] Y. LE PENTREC, G. LAURIAT, *Effects of the heat transfer at the side walls on natural convection in cavities*. J. Heat Trans., 112 (1990), no. 2, 370–378.

- [35] P. LENARDA, M. PAGGI, R. RUIZ-BAIER, *Partitioned coupling of advection-diffusion-reaction systems and Brinkman flows*. J. Comput. Phys., 344 (2017), 281–302.
- [36] X. MA, Z. TAO, T. ZHANG, *A variational multiscale method for steady natural convection problem based on two-grid discretization*. Adv. Diff. Eqns., (2016), 2–20.
- [37] H. MADER, E. LLEWELLIN, S. MUELLER, *The rheology of two-phase magmas: A review and analysis*. J. Volc. Geotherm. Res., 257 (2013), 135–158.
- [38] R. OYARZÚA, T. QIN, D. SCHÖTZAU, *An exactly divergence-free finite element method for a generalized Boussinesq problem*. IMA J. Numer. Anal., 34 (2014), no. 3, 1104–1135.
- [39] R. OYARZÚA, P. ZÚÑIGA, *Analysis of a conforming finite element method for the Boussinesq problem with temperature-dependent parameters*. J. Comput. Appl. Math., 323 (2017), 71–94.
- [40] H.M. QUINN, *A reconciliation of packed column permeability data: Column permeability as a function of particle porosity*. J. Materials (2014), 636507.
- [41] R. ROSCOE, *The viscosity of suspensions of rigid spheres*, Brit. J. Appl. Phys., 3 (1952), 267–269.
- [42] R. RUIZ-BAIER, H. TORRES, *Numerical solution of a multidimensional sedimentation problem using finite volume-element methods*. Appl. Numer. Math., 95 (2015), 280–291.
- [43] P.W. SCHROEDER, G. LUBE, *Stabilised dG-FEM for incompressible natural convection flows with boundary and moving interior layers on non-adapted meshes*. J. Comput. Phys., 335 (2017), 760–779.
- [44] M.A. SHEREMET, T. GROSAN, I. POP, *Natural convection and entropy generation in a square cavity with variable temperature side walls filled with a nanofluid: Buongiorno’s mathematical model*. Entropy, 19 (2017), 337.
- [45] M. TABATA, D. TAGAMI, *Error estimates of finite element methods for nonstationary thermal convection problems with temperature-dependent coefficients*. Numer. Math., 100 (2005), 351–372.
- [46] M. ULVROVÁ, S. LABROSSE, N. COLTICE, P. RØABACK, P.J. TACKLEY, *Numerical modelling of convection interacting with a melting and solidification front: Application to the thermal evolution of the basal magma ocean*. Phys. Earth Planet. Inter. 206-207 (2012), 51–66.
- [47] R.T. WALKER, D. M. HOLLAND, *A two-dimensional coupled model for ice shelf–ocean interaction*. Ocean Model., 17 (2007), 123–139.
- [48] D.C. WAN, B.S.V. PATNAIK, G.W. WEI, *A new benchmark quality solution for the buoyancy-driven cavity by discrete singular convolution*. Numerical Heat Transfer B, 40 (2001), 199–228.
- [49] S. WANG, A. FAGHRI, T.L. BERGMAN, *A comprehensive numerical model for melting with natural convection*. Int. J. Heat Mass Transfer, 53 (2010), no. 9-10, 1986–2000.
- [50] Y. ZHANG, Y. HOU, H. JIA, *Subgrid stabilized defect-correction method for a steady-state natural convection problem*. Comp. Math. Appl., 67 (2014), 497–514.

Centro de Investigación en Ingeniería Matemática (CI²MA)

PRE-PUBLICACIONES 2018

- 2018-15 VERONICA ANAYA, MOSTAFA BENDAHMANE, DAVID MORA, MAURICIO SEPÚLVEDA: *A virtual element method for a nonlocal FitzHugh-Nagumo model of cardiac electrophysiology*
- 2018-16 TOMÁS BARRIOS, ROMMEL BUSTINZA: *An a priori error analysis for discontinuous Lagrangian finite elements applied to nonconforming dual mixed formulations: Poisson and Stokes problems*
- 2018-17 RAIMUND BÜRGER, GERARDO CHOWELL, ELVIS GAVILÁN, PEP MULET, LUIS M. VILLADA: *Numerical solution of a spatio-temporal predator-prey model with infected prey*
- 2018-18 JAVIER A. ALMONACID, GABRIEL N. GATICA, RICARDO OYARZÚA, RICARDO RUIZ-BAIER: *A new mixed finite element method for the n-dimensional Boussinesq problem with temperature-dependent viscosity*
- 2018-19 ANTONIO BAEZA, RAIMUND BÜRGER, MARÍA CARMEN MARTÍ, PEP MULET, DAVID ZORÍO: *Approximate implicit Taylor methods for ODEs*
- 2018-20 RAIMUND BÜRGER, DANIEL INZUNZA, PEP MULET, LUIS M. VILLADA: *Implicit-explicit schemes for nonlinear nonlocal equations with a gradient flow structure in one space dimension*
- 2018-21 RICARDO OYARZÚA, MIGUEL SERÓN: *A divergence-conforming DG-mixed finite element method for the stationary Boussinesq problem*
- 2018-22 VERONICA ANAYA, AFAF BOUHARGUANE, DAVID MORA, CARLOS REALES, RICARDO RUIZ-BAIER, NOUR SELOULA, HECTOR TORRES: *Analysis and approximation of a vorticity-velocity-pressure formulation for the Oseen equations*
- 2018-23 ANA ALONSO-RODRIGUEZ, JESSIKA CAMAÑO, EDUARDO DE LOS SANTOS, FRANCESC RAPETTI: *A graph approach for the construction of high order divergence-free Raviart-Thomas finite elements*
- 2018-24 RAIMUND BÜRGER, PAUL E. MÉNDEZ, CARLOS PARÉS: *On entropy stable schemes for degenerate parabolic multispecies kinematic flow models*
- 2018-25 JESSIKA CAMAÑO, CARLOS GARCIA, RICARDO OYARZÚA: *Analysis of a conservative mixed-FEM for the stationary Navier-Stokes problem*
- 2018-26 MARIO ÁLVAREZ, BRYAN GOMEZ-VARGAS, RICARDO RUIZ-BAIER, JAMES WOODFIELD: *Stability and finite element approximation of phase change models for natural convection in porous media*

Para obtener copias de las Pre-Publicaciones, escribir o llamar a: DIRECTOR, CENTRO DE INVESTIGACIÓN EN INGENIERÍA MATEMÁTICA, UNIVERSIDAD DE CONCEPCIÓN, CASILLA 160-C, CONCEPCIÓN, CHILE, TEL.: 41-2661324, o bien, visitar la página web del centro: <http://www.ci2ma.udec.cl>



**CENTRO DE INVESTIGACIÓN EN
INGENIERÍA MATEMÁTICA (CI²MA)**
Universidad de Concepción



Casilla 160-C, Concepción, Chile
Tel.: 56-41-2661324/2661554/2661316
<http://www.ci2ma.udec.cl>

